pe Holes

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.1. Approval expires 11-30-49.
Land Office
Lease No. 0690 52
Timit

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Indicate Above By CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) James 7 5	Subsequent report of shorting casing. Subsequent report of reprilling or repair. Subsequent report of report. Subsequent report of reprilling or repair. Subsequent report of reprilling or repair. Subsequent report of report. Subsequent report of reprilling or repair. Subsequent report of report. Subsequent report of reprilling or repair. Subsequent report of report. Subsequent report of rep	OTICE OF INTENTION TO	CHANGE PLANS TEST WATER SHUT-OFF PRE-DRILL OR REPAIR WELL SHOOT OR ACIDIZE OPULL OR ALTER CASING ABANDON WELL (INDICATE ABOVE BY CHECK	SUBSEQUENT REPORT OF SHOOTING OR ACIDING SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF REDRILLING OR REPAIR. SUBSEQUENT REPORT OF ABANDONMENT. SUPPLEMENTARY WELL HISTORY. MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) JERUS 5	
SUBSEQUENT REPORT OF ALTERING OR REPAIR. SUBSEQUENT REPORT OF ALTERNOOPER. SUBSEQUENT REPORT OF ALERNOOPER. SUBSEQUENT REPORT OF ALERNOOPER. SUBSEQUENT REPORT OF ALERNOOPER. SUBSEQUENT R	SUBSEQUENT REPORT OF ALTERING OR REPAIR. SUBSEQUENT REPORT OF ALERING. SUBSEQUENT REPORT OF ALTERING OR REPAIR. SUBSEQUENT REPORT OF ALTERING OR REPAIR. SUBSEQUENT REPORT OF ALTERING OR REPAIR. SUBSEQUENT REPORT OF ALERING. SUBSEQUENT REPORT OF ALTERING OR REPAIR. SUBSEQUENT REPORT OF ALERING. SUBSEQUENT REPORT OF ALERIN	OTICE OF INTENTION TO	CHANGE PLANS TEST WATER SHUT-OFF PRE-DRILL OR REPAIR WELL SHOOT OR ACIDIZE OPULL OR ALTER CASING ABANDON WELL (INDICATE ABOVE BY CHECK	SUBSEQUENT REPORT OF ALTERING CASING- SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) JUBLICATION	
Subsequent report of redrilling or redrilling or report of redrilling or	SUBSEQUENT REPORT OF REDRILLING ON THE SUBSEQUENT REPORT OF REDRILLING ON THE SUBSEQUENT REPORT OF ABANDONMENT. SUBSEQUE	OTICE OF INTENTION TO OTICE OF INTENTION TO OTICE OF INTENTION TO OTICE OF INTENTION TO OTICE OF INTENTION T	O RE-DRILL OR REPAIR WELL O SHOOT OR ACIDIZE O PULL OR ALTER CASING O ABANDON WELL (INDICATE ABOVE BY CHECK	SUBSEQUENT REPORT OF REDRILLING ON THE SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY	
The elevation of the derrick floor above sea level is	The elevation of the derrick floor above sea level is	OTICE OF INTENTION TO OTICE OF INTENTION TO OTICE OF INTENTION TO IOTICE OF INTENTION TO	O RE-DRILL OR RELATION O SHOOT OR ACIDIZE O PULL OR ALTER CASING O ABANDON WELL (INDICATE ABOVE BY CHECK	SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY	
Supplementary well history. It and 1650 It and 1650 It and 1650 It from Supplementary. It and 1650 It and 1650 It and 1650 It and 1650	Supplementary well history. It and 1650 It and 1650 It and 1650 It from Supplementary. It and 1650 It and 1650 It and 1650 It and 1650	OTICE OF INTENTION TO OTICE OF INTENTION TO IOTICE OF INTENTION TO	(INDICATE ABOVE BY CHECK	SUPPLEMENTARY WELL HISTORY MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) JERSINY 5	
Well No. 780 is located 480 ft. from \$\begin{array}{c} \liming \text{line and } \text{150} \text{ from \$\begin{array}{c} \text	Well No. 780 is located 480 ft. from \$\begin{array}{c} \liming \text{line and } \text{150} \text{ from \$\begin{array}{c} \text	IOTICE OF INTENTION TO	(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
Vell No. 78D is located 480 ft. from S line and 1650 ft. from S line and 1650 ft. from S line of sec. 31 Vell No. 78D is located 480 ft. from S line and 1650 ft. from S line of sec. 31 (M Sec. and Sec. No.) (Twp.) (Range) (Meridian) (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comer important proposed work) (State names of and expected depths to objective sands; ahow sizes, weights, and lengths of proposed casings; indicate mudding jobs, comer propose to drill this test to a depth of 6750 drilling a 13 3/4 hole to propose to drill this test to a depth of 6750 drilling a 13 3/4 hole to propose to drill this test to a depth of 6750 casing with sufficient proposed to drill this test to a depth of 6750 casing with sufficient cases to circulate. We will drill a 9/18 bole and cases to case the sufficient case to circulate. We will drill a 9/18 bole and cases to case the sufficient case to circulate. We will drill a 9/18 bole and case to the sufficient case to circulate. We will drill a 9/18 bole and case to the sufficient case to circulate. We will drill a 9/18 bole and case to the sufficient case to circulate. We will drill a 9/18 bole and the bole	Vell No. 78D is located 480 ft. from S line and 1650 ft. from S line and 1650 ft. from S line of sec. 31 Vell No. 78D is located 480 ft. from S line and 1650 ft. from S line of sec. 31 (M Sec. and Sec. No.) (Twp.) (Range) (Meridian) (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemer ing points, and all other important proposed work) Propose to drill this test to a depth of 6750 drilling a 13 3/4% hole to propose to drill this test to a depth of 6750 drilling a 13 3/4% hole to care to circulate. We will drill a 9/4% hole and cement 7 5/8 24 casing proving the second of the	NOTICE OF INTENTION T	(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) JERRINTY 5	10 54
Vell No. 780 is located 60 ft. from 8 line and 650 ft. from W line of sec. 31 Vell No. 780 is located 60 ft. from 8 line and 650 ft. from W line of sec. 31 (W. Sec. and Sec. No.) (Twp.) (Range) (Meridian) (Pield) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comer ing points, and all other important proposed work) Propose to drill this test to 2 depth of 6750 drilling 2 13 3/6 hole to proving the subdivision of the sand coment and c	Vell No. 780 is located 60 ft. from S line and 650 ft. from W line of sec. 31 Vell No. 780 is located 60 ft. from S line and 650 ft. from W line of sec. 31 (W. Sec. and Sec. No.) (Twp.) (Range) (Meridian) (Pield) (County or Subdivision) (State or Territory) (S		(INDICATE ABOVE BY CHECK	Jaminty 5	10 54
Vell No. 780 is located 160 ft. from S line and 1650 ft. from W line of sec. 31 188 328	Vell No. 780 is located 180 ft. from S line and 1650 ft. from W line of sec. 31 184 32			Jaminty 5	10 24
In the levation of the derick floor above sea level is	Interest				
Vell No. 780 is located 180 ft. from S line and 1650 ft. from W line of sec. 31	Vell No. 780 is located 180 ft. from S line and 1650 ft. from W line of sec. 31				
(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comer ing points, and all other important proposed work) propose to drill this test to a depth of 6750 drilling a 13 3/4" hole to provide depth of 200 and comenting 10 3/4" 32.755 casing with sufficient provide depth of 200 and comenting 10 3/4" all cannot coment 7 5/8 244 casing provide to circulate. We will drill a 9 7/8" hole and coment 7 5/8 244 casing provide to circulate. We will drill a 9 7/8" hole and coment 7 5/8 244 casing provide to circulate. We will drill a 9 7/8" hole and coment will be approximately 3100 isolating the salt section by stage coment will be approximately 3100 isolating the salt section by stage coment will be	(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen ing points, and all other important proposed work) propose to drill this test to a depth of 6750 drilling a 13 3/4% hole to provide depth of 200 and cementing 10 3/4% 32.755 casing with sufficient provide depth of 200 and cementing 10 3/4% 32.755 casing with sufficient provide depth of 200 and cementing 10 3/4% 32.755 casing with sufficient provide depth of 200 and cementing 10 3/4% bole and cement 7 5/8 24% casing provide to circulate. We will drill a 9 7/8% hole and cementing. We will seem to circulate. We will drill a 9 8/8% bole and cementing. We will seem to circulate. We will drill a 9 8/8% bole and cementing. We will be approximately 3100 isolating the salt section by stage cement will be	·(TV -1.3)			
(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicated ing points, and all other important proposed work) a propose to drill this test to a depth of 6750 drilling a 13 3/4" hole to proving the depth of 200 and comenting 10 3/4" 32.755 casing with sufficient proving the depth of 200 and comenting 10 3/4" hole and coment 7 5/8: 244 casing proving to circulate. We will drill a 9 7/8" hole and coment 7 5/8: 244 casing the control to circulate. We will drill a 9 7/8" hole and comenting. We will be approximately 3100 isolating the salt section by stage coment will be approximately 3100 isolating the salt section by stage coment will be	(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicated ing points, and all other important proposed work) a propose to drill this test to a depth of 6750 drilling a 13 3/4" hole to proving the depth of 200 and comenting 10 3/4" 22.755 casing with sufficient proving to depth of 200 and comenting 10 3/4" hole and coment 7 5/8 244 casing proving to circulate. We will drill a 9 7/8" hole and coment 7 5/8 244 casing the salt section by stage comenting. We will emproving the salt section by stage coment will be approximately 3100 isolating the salt section by stage coment will be	The elevation of t	the derrick floor above	sea level is	
e propose to drill this test counting 10 3/4" 32.75 canent 7 5/8" 244 caning proximate depth of 200' and comenting 10 7/8" hole and coment 7 5/8" 244 caning proximate depth of 200' and comenting we will seem to circulate. We will drill a 9 7/8" hole and coment of the will be comentately 3100' isolating the salt section by stage coment will be comparisonably 3100' isolating the salt section by stage coment will be comparisonably 3100' isolating the salt section by stage coment on 55".	propose to drill this test counting 10 3/4 32.75 canent 7 5/8 24 casing proximate depth of 200 and comenting 10 3/4 hole and coment 7 5/8 24 casing proximate depth of 200 and comenting the salt section by stage comenting. We will ement to circulate. We will be salt section by stage comenting. We will be approximately 3100 isolating the salt section by stage coment will be approximately 3100 isolating the salt section by stage coment will be			1 langths of proposed casings; indicate	ding jobs, comen
e propose to drill this test comenting 10 3/4" 32.75 cenent 7 5/8" 244 casing proximate depth of 200' and cementing 10 3/8" hole and cement 7 5/8" 244 casing proximate depth of 200' and drill a 9 7/8" hole and cement 7 5/8" 244 casing proximate to circulate. We will a section by stage cementing. We will be coment to circulate. We will be comentately 3100' isolating the salt section by stage cement will be comentately 3100' isolating the salt section by stage cement will be comparable to circulate the salt section by stage cement of 5/8".	e propose to drill this test comenting 10 3/4" 32.77 cement 7 5/8" 204 casing pproximate depth of 200' and comenting 10 7/8" hole and cement 7 5/8" 204 casing pproximate depth of 200' and comenting by stage comenting. We will be	(State names of and exp	ected depths to objective sands ing points	s; show all other important proposed work,	le to
		e propose to deprovimente des	oth of 200 and contact. So will dr	menting 10 7/8" hole and cement 7 5/8" 24 111 a 9 7/8" hole and cement 7 5/8" 24 the salt section by stage cementing. the salt section by stage cementing. The salt section by stage cement were the salt section by stage cement were section by stage cement were salt section and the hours on	Ye vill
		allowed to set	a vill be pressure		
Ceological Survey before operations may be commence	Ceological Survey before operations may be commence	allowed to set	a vill be pressure		
t and that this plan of work must receive approval in writing by the Geological Survey before operations may be commence	that this plan of work must receive approval in writing by the Geological Survey before operations may be commence	allowed to set	a vill be pressure		
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commence	I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commence	allowed to set	this plan of work must receive	e approval in writing by the Geological Survey before operations ma	
L. B. Millow	I. S. Millor	allowed to set	this plan of work must receive	e approval in writing by the Geological Survey before operations ma	
Company	Company	l understand tha	t this plan of work must receive	e approval in writing by the Geological Survey before operations ma	
L. B. Millou	Company	I understand that	t this plan of work must receive L. B. Elliets Box 703	e approval in writing by the Geological Survey before operations ma	

Harman Market Ma