Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions re- verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [X] GAS WELL [ ] OTHER

2. NAME OF OPERATOR
Skelly Oil Company

3. ADDRESS OF OPERATOR
P. O. Box 1351, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
Unit Letter "H", 2310' FNL and 660' FEL, Section 31-24S-38E

5. LEASE DESIGNATION AND SERIAL NO.
LC-069052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
- - - - - - - -

7. UNIT AGREEMENT NAME
West Dollarhide Queen Sand Unit

8. FARM OR LEASE NAME
West Dollarhide Queen Sand Unit

9. WELL NO.
31

10. FIELD AND POOL, OR WILDCAT
Dollarhide

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 31-24S-38E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3139' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[ ]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[X]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other)			
(Other)			[ ]	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1) Moved in pulling unit 2-4-74.
2) Set cast iron bridge plug at 3440' and capped with 25 sacks of cement to 3225'.
3) Spotted 35 sack cement plug 2306-2605'.
4) Perforated 5-1/2" casing with two shots at 1300'.
5) Squeezed with 75 sacks of cement, displaced to 1100', leaving 200' of cement inside 5-1/2" casing.
6) Spotted 10 sack cement plug from surface to 15'.
7) Installed dry hole marker.

All intervals not cemented were filled with 10# mud. No casing was pulled. The 10-3/4" OD 32.75# casing, set at 206' and the 5-1/2" OD 14# casing, set at 3650' were left in the hole. Well plugged and abandoned 2-6-74.

18. I hereby certify that the foregoing is true and correct

SIGNED (Signed) D. R. Crow TITLE Lead Clerk DATE 2-12-74

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

☆ GPO 782-930