


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 10002
Unit 1



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 1, 1954

Well No. 2 is located 300 ft. from N line and 900 ft. from E line of sec. 31
El Paso, Sec. 31 (1/4 Sec. and Sec. No.)
Hollabrite mesa (Field)
24N (Twp.)
28E (Range)
100M (Meridian)
Lea (County or Subdivision)
New Mexico (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a 11" hole to depth of 215 feet and cement 8 5/8" 18' casing on bottom with sufficient cement to circulate. We will drill a 8 3/4" hole below surface casing to an approximate depth of 9700' and cement 5 1/2" 14' casing with an estimated amount of cement to return to base of surface casing. We will allow 24 hours C.C.C. on surface and 48 hours on setting. All cement jobs will be tested according to regulations. Estimated total depth is 9745'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sunshine Royalty Company

Address Box 147

Hollabrite, N. Mexico

By

Title Vice President