

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-79

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water injection well	7. Unit Agreement Name West Dollarhide Queen Sand Unit
2. Name of Operator Sirgo-Collier, Inc.	8. Farm or Lease Name
3. Address of Operator P. O. Box 3531, Midland, Texas 79702	9. Well No. 46
4. Location of well UNIT LETTER P 330 FEET FROM THE South LINE AND 330 FEET FROM THE East LINE, SECTION 31 TOWNSHIP 24S RANGE 38E NMPM.	10. Field and Pool, or Wildcat Dollarhide Queen
11. Elevation (Show whether DF, RT, GR, etc.) 3130' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER Cement 4-1/2" casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-24-88 Deepened to TD of 3950'.

3-2-88 Ran 96 joints of 4-1/2" 10.5# casing to 3950'. Cemented first stage with 100 sx Class "C" with 2% CaCl2. Circulated 40 sx. Cemented second stage with 300 sx Halliburton Light with 0.5% CFR-3, tailed with 100 sx Class "C" with 2% CaCl2. Circulated 98 sx.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry L. Whitley TITLE Agent DATE March 7, 1988

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY: \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAR 10 1988

CONDITIONS OF APPROVAL, IF ANY: