

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

(Form C-104)
Revised 7/1/57

REQUEST FOR (OIL) - (GAS) ALLOWABLE

New Well
Recompletion

This form shall be submitted by the operator before an initial allowable will be assigned to any completed Oil or Gas well. Form C-104 is to be submitted in QUADRUPLICATE to the same District Office to which Form C-101 was sent. The allowable will be assigned effective 7:00 A.M. on date of completion or recompletion, provided this form is filed during calendar month of completion or recompletion. The completion date shall be that date in the case of an oil well when new oil is delivered into the stock tanks. Gas must be reported on 15.025 psia at 60° Fahrenheit.

Hobbs, New Mexico - March 18, 1958

(Place) (Date)

WE ARE HEREBY REQUESTING AN ALLOWABLE FOR A WELL KNOWN AS:

Skelly Oil Company Mexico "J", Well No. 1, in SE 1/4 SE 1/4,

(Company or Operator) (Lease)
n.p.m. Sec. 32, T. 24S, R. 38E, NMPM., Dollarhide-Fusselman Pool

Unit Letter
Lea

County. Date Spudded May 4, 1951 Date Drilling Completed August 17, 1951
Elevation 5180' D.F. Total Depth 10,245' PBD 8760'

Please indicate location:

D	C	B	A
E	F	G	H
L	K	J	I
M	N	O	P x

660' FSL & 660' FEL

Top Oil/Gas Pay 8704' Name of Prod. Form. Fusselman

PRODUCING INTERVAL -

Perforations 8704-8724'

Open Hole Depth 10,243 1/2' Casing Shoe Depth 5830' Tubing

OIL WELL TEST -

Natural Prod. Test: bbls. oil, bbls water in hrs, min. Size Choke

Test After Acid or Fracture Treatment (after recovery of volume of oil equal to volume of load oil used): 50 bbls. oil, 27 bbls water in 24 hrs, 0 min. Size Choke

GAS WELL TEST -

Natural Prod. Test: MCF/Day; Hours flowed Choke Size

Method of Testing (pitot, back pressure, etc.):

Test After Acid or Fracture Treatment: MCF/Day; Hours flowed

Choke Size Method of Testing:

Acid or Fracture Treatment (Give amounts of materials used, such as acid, water, oil, and sand): Acidized perforations 8704-8724' with 500 Gallons Mud Acid

Casing Tubing Date first new March 15, 1958
Press. oil run to tanks

Oil Transporter Texas-New Mexico Pipeline Company

Gas Transporter El Paso Natural Gas Company

Remarks: Set model "N" Baker cast iron bridging plug at 8760'. Acidized new casing perforations 8704-8724' with 500 gallons Mud Acid. After recovering load oil, well pumped 50 barrels oil and 27 barrels sulphur water in 24 hours.

I hereby certify that the information given above is true and complete to the best of my knowledge.

Approved: 19

Skelly Oil Company

(Company or Operator)

OIL CONSERVATION COMMISSION

By: [Signature]

Title

By: [Signature]
(Signature)

Title District Superintendent

Send Communications regarding well to:

Skelly Oil Company

Name

Address Box 38 - Hobbs, New Mexico