

EW MEXICO OIL CONSERVATION COMMISSION

SANTA EE NEW MEXICO

MISCELLANEOUS NOTICES

RECEIVED
MAY - 7 1951

SHUT-OFF NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING			OS NOTIC	3	OF CONSERVAT	DON POMERICON
Indicate nature of notice by checking below: NOTICE OF INTENTION TO TEST CASING SHUTOFF NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING NOTICE OF INTENTION TO PLUG WELL NOTICE OF INTENTION TO DEEPEN WELL NOTICE OF INTENTION TO DEEPEN WELL NOTICE OF INTENTION TO PLUG WELL NOTICE OF INTENTION TO SHOULD TO PLUG WELL NOTICE OF INTENTION TO SHOULD TO PLUG WELL NOTICE OF INTENTION TO SHOULD TO PLUG WELL NOTICE OF INTENTION	advicable on the rejection by the Commission of	 agent, of th 	ie blan submitted. 🗀	rne pian as ap	provea snouia	De Tonower,
NOTICE OF INTENTION TO TEST CASING SHUT-OFF SHUT		obtained. See	additional instruc	tions in the	Rules and Re	guiations of
SHUT-OFF NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO PLUL OR OTHERWISE ALTER CASING NOTICE OF INTENTION TO DEEPEN WELL Hobbs, New Mexico Gentlemen: Hobbs, New Mexico Gentlemen: Following is a notice of intention to do certain work as described below at the Skelly Oll Compeny Company or Operator Leas FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291'. Ran 13-3/8" OD. casing to 291' and consented with 300 sacks. The Halliburton process was used and coment was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test easing shut-off. NOTICE OF INTENTION TO PLUL OR NOTICE O	Indicate n	ature of noti	ce by checking belo	w:		
NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO REPAIR WELL NOTICE OF INTENTION TO PLUG WELL N	NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X				
NOTICE OF INTENTION TO DEEPEN WELL Hobbs, New Mexico Onl CONSERVATION COMMISSION, Santa Pe, New Mexico Gentlemen: Following is a notice of intention to do certain work as described below at the Skelly 011 Compeny Company or operator Of Sec. 32 T. 24S R. 38E N. M. P. M. Will No. 1 in CSE/A SE/A FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291'. Ran 13-3/8" OD. casing to 291' and cements with 300 sacks. The Halltburton process was used and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test easing shut-off. Approved Approved Approved Approved OIL CONSERVATION COMMISSION, By Dist. Supt. Send communications regarding well to Name Skelly 0.1 Company FORM MAY -7 100'' Skelly Oil Company Company or Operator Name Skelly 0.1 Company Form Address Drawer *Br* Hobbs, New Mexico		3				
Hobbs, New Mexics Place April 5, 1951 Date OIL CONSERVATION COMMISSION, Santa Fe, New Mexico Gentlemen: Following is a notice of intention to do certain work as described below at the Nection "J" Well No. 1 in CSE/A SE/A Sec. 12 2.5 R 36E N.M.P.M. Wildcat Field. Lea County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291°. Ram 13-3/8° OD. casing to 291° and cemented with 300 sacks. The Halliburton process was used and cement was circulated back to surface. Hill let cement set approximately 36 hours and on May 6, 1951 at 11:00 FM. will drill plug and test easing similaries. Approved. Approved. Approved. Approved. OIL CONSERVATION COMMISSION. By Wally OllCorpusy Coppsay or Operator Send communications regarding well to Name Skelly Oll Correctly Name Skelly Oll Correctly Hobbs, New Mexico	NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL			
OIL CONSERVATION COMMISSION. Santa Fe, New Mexico Gentlemen: Following is a notice of intention to do certain work as described below at the Security Oil Company Mexico "J" Well No. 1 in CSE/4 SE/4 Company or Operator FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291°. Ram 13-3/8" OD. casing to 291° and cemented with 300 sacks. The Halliburton process we suced and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will cirill plug and test easing sheat-off. Approved. MAY -7 10° 19. Skelly OilCompany Approved. Position Diet. Supt. Send communications regarding well to Skelly Oil Connerty OIL CONSERVATION COMMISSION. Name Skelly Oil Company Address Drawer "B" Hobbs, New Mexico	NOTICE OF INTENTION TO DEEPEN WELL					
OIL CONSERVATION COMMISSION. Santa Fe, New Mexico Gentlemen: Following is a notice of intention to do certain work as described below at the Security Oil Company Mexico "J" Well No. 1 in CSE/4 SE/4 Company or Operator FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291°. Ram 13-3/8" OD. casing to 291° and cemented with 300 sacks. The Halliburton process we suced and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will cirill plug and test easing sheat-off. Approved. MAY -7 10° 19. Skelly OilCompany Approved. Position Diet. Supt. Send communications regarding well to Skelly Oil Connerty OIL CONSERVATION COMMISSION. Name Skelly Oil Company Address Drawer "B" Hobbs, New Mexico		Hob	bs, New Mexico	0	April 5,	1951
Santa Fe, New Mexico Gentiemen: Shelly 011 Company Nexteo "J" Well No. 1 in CSE/A SE/A Skelly 011 Company Nexteo "J" Well No. 1 in CSE/A SE/A Company or Operator Of Sec. 32 T. 2A5 R. 38E N. M. P. M. Vildcat Field. Lea County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291°. Sam 13-3/8° OD. casing to 291° and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test easing shat-off. Approved. Except at follows: MAY -7 105° Approved. Except at follows: Diet. Supt. Send communications regarding well to Skelly 0.1 Company OIL CONSERVATION COMMISSION, Name Skelly 0.1 Company Address Drawer "D" Hobbs, New Hexico					Date	
Gentlemen: Following is a notice of intention to do certain work as described below at the Skelly Oil Company or Operator Skelly Oil Company or Operator Company or Operator Of Sec. 32 T. 245 R. 365 N. M. P. M. Vildcat Full DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291°. Ram 13-3/8° OD. casing to 291° and cemented with 300 sacks. The Halliburton process was used and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 FM. will drill plug and test casing shut-off. Approved. Approved. Position Oil Conservation Commission. Name Skelly Oil Company Company or Operator By Dist. Supt. Send communications regarding well to Skelly Oil Company Dist. Supt. Send communications regarding well to Traver "D" Hobbs, New Hexico						
Skelly 011 Company of Operator Company of Operator Of Sec. 32 T. 248 R. 38E N. M. P. M. Vildcat FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291'. Ran 13-3/8" OD. casing to 291' and cemented with 300 cacks. The Halliburton process was used and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test casing shat-off. Approved. Approved. Position Dist. Supt. Send communications regarding well to Skelly 0.1 Company OIL CONSERVATION COMMISSION. By Warney May Address Drayer **Drill* Hobbs, New Mexico						
of Sec. 22 T 24.5 R 38E N. M. P. M. Vildcat Field. Lea County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291'. Ram 13-3/8" OD. casing to 291' and cemented with 300 sacks. The Halliburton process was used and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test easing shat-off. Approved. NAAY - 7 10C1 Skelly OliCompany Position Dist. Supt. Send communications regarding well to Name Skelly Oli Company Address Traver *DH* Hobbs, New Mexico	Following is a notice of intention to do certain Skelly 011 Company	work as desc	cribed below at the	Well N	[o1	CSE/4 SE/4
FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291'. Ram 13-3/8" OD. casing to 291' and cemented with 300 sacks. The Halliburton process was used and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test easing shat-off. Approved						
FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Drilled to total depth of 291'. Ram 13-3/8" OD. casing to 291' and cemented with 300 sacks. The Halliburton process was used and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test easing shat-off. Approved	*		N. M. P. M.,			Field.
Drilled to total depth of 291'. Ran 13-3/8" OD. casing to 291' and cemented with 3CO sacks. The Halliburton process was used and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test casing shut-off. Approved		_				
Drilled to total depth of 291'. Ram 13-3/8" OD. casing to 291' and cemented with 300 sacks. The Halliburton process was used and cement was circulated back to surface. Will let cement set approximately 36 hours and on May 6, 1951 at 11:00 PM. will drill plug and test casing shut-off. Approved						
Approved	FOLLOW INSTRUCTIONS IN T	HE RULES	AND REGULATION	NS OF THE C	COMMISSION	
Position Dist. Supt. Position Send communications regarding well to OIL CONSERVATION COMMISSION, By Name Skelly 0,1 Company Address Drawer DR Hobbs, New Mexico	cemented with 300 sacks. was circulated back to so 36 hours and on May 6, 19 casing shut-off.	The Hall prface. V	Hill let cement of the control of the control of the centrol of th	ess was use at set appi irill plug	ed and come reschmately and test	rat.
By Dist. Supt. Position Dist. Supt. Send communications regarding well to Name Skelly 0 1 Company Address Dravier DR Hobbs, New Mexico	Approved MAY - 7	19	Skel	Z		
OIL CONSERVATION COMMISSION, Name Skelly 0 1 Company Address By Row Mexico				Comp	1/0/8/	
OIL CONSERVATION COMMISSION, Name Skelly 0 1 Company Address By Row Mexico			Ву	<u> </u>	i aurice	******
By Roll yard of Address Braver BDH Address Hobbs, New Mexico			Position Ser			well to
By Roll yards Address Draver DH Hobbs, New Mexico	OIL CONSERVATION COMMISSION	N.	Name	Skelly 0 l	Company	
	By Roll markousk	7	•	Draver *D#		
	Title Oil & Gas Inspec	ctor	. <u></u> i	Hobbs, New	Mexico	