| NO. OF COPIES RECEIVED | | |
|---|---|---|
| DISTRIBUTION | | |
| SANTA FE | | |
| FILE | | |
| U.S.G.S. | | |
| LAND OFFICE | | |
| OPERATOR | | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State [X] Fee [ ]

5. State Oil & Gas Lease No.
B-9311

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT —" FORM C-101) FOR SUCH PROPOSALS.)

7. Unit Agreement Name
West Dollarhide Drk. Unit

OIL WELL [X] GAS WELL [ ] OTHER-

8. Farm or Lease Name
West Dollarhide Drk. Unit

2. Name of Operator
Getty Oil Company

9. Well No.
68

3. Address of Operator
P. O. Box 730, Hobbs, New Mexico 88240

10. Field and Pool, or Wildcat
Dollarhide Tubb-Drinkard

4. Location of Well
UNIT LETTER M, 660 FEET FROM THE South LINE AND 660 FEET FROM THE WEST LINE, SECTION 32 TOWNSHIP 24S RANGE 38E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3147' DF

12. County
Lea

6. Check Appropriate Box To Indicate N 0+2

NOTICE OF INTENTION TO:

| | | | |
|---|---|---|---|
| PERFORM REMEDIAL WORK | [ ] | PLUG AND ABANDON | [ ] |
| TEMPORARILY ABANDON | [ ] | | |
| PULL OR ALTER CASING | [ ] | CHANGE PLANS | [ ] |
| OTHER Recement casing | [X] | | |

P.O. BOX 1980
HOBBS, N.M. 88240 (LEA COUNTY)

1-R.J. STARRAK-TULSA
1-A.B. CARY-MIDLAND
1-E. Buttress, ENGINEER
1-C. Kingston, FOREMAN - West Dollarhide Drinkard Unit
1-FILE
1- ———, WIO's -LIST ATTACHED
1-BH, FIELD CLERK

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Rig up pulling unit.
2. Pull rods and pump.
3. Install BOP and pull tubing.
4. Run retrievable BP to approximately 6000'. Test BP and casing to 1000 psi.
5. Spot 10' of sand on top of BP.
6. Run cement bond log 6000' to surface.
7. Perforate and cement squeeze intervals not adequately cemented.
8. WOC 24 hrs.
9. Drill out cement and test casing to 1000 psi.
10. Wash sand off BP and retrieve.
11. Run tubing, rods, and pump and place back on production.

THE COMMISSION MUST BE NOTIFIED
24 HOURS PRIOR TO COMMENCING WORK

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert A. Parker TITLE Area Superintendent DATE 8-17-78

APPROVED BY Orig. Signed by Jerry Sexton Dist. I, Supv. TITLE SUPERVISOR DISTRICT I DATE AUG 21 1978

CONDITIONS OF APPROVAL, IF ANY: