

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 12-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

0+6-NMOCD-Hobbs 1-Mr. J.A.-Midland
1-File 1-Laura Richardson
1-Engr Jim 1-BB
1-Foreman CK 1-JA

1a. Indicate Type of Lease
State ☒ For ☐
5. State Oil & Gas Lease No.
B-9311

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER- Well Name Change (Old Name Mexico J #23)	7. Unit Agreement Name West Dollarhide Drinkard
2. Name of Operator Getty Oil Company	8. Farm or Lease Name
3. Address of Operator P.O. Box 730, Hobbs, NM 88240	9. Well No. 89
4. Location of Well UNIT LETTER <u>O</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1830</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>24S</u> RANGE <u>38E</u> NMPM.	10. Well Name <i>Dollarhide Drinkard</i>
15. Elevation (Show whether DF, RT, GR, etc.) 3619' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/15/83 Ran GR-CNL 7167-5000' set CI plug @ 7420'. Perf Drinkard 6357, 65, 66, 68, 74, 82, 84, 88, 89, 97, 6405, 17, 22, 31, 32, 46, 55, 57, 70, 72, 80, 90, = 2 shots per foot = 44 shots. Dump 4 sxs of cement BP 7385' ran tbq & pkr to 1240'.

11/17/83 Treated perfs 6357-6490 w/ 4700 gal 15%, 80 balls, ball out w/ 56 balls, max 5000#, Avg 3600#, rate 5 bbls / min. SI 1650#. 15 min 1520#, total load 142 bbls.

11/18/83 TIH w/ mud anchor, perfed sub, SN, tbq anchor and 96 joints of tbq.

11/21/83 12 hours, 7 1/2 x 144, 1 1/2 pump, 64 1/2 BO, 95.6 BW, 5.37 MCF.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed *Jerry Sexton* Title Area Superintendent Date November 29, 1983
Date 8-1-83 Crockett

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT SUPERVISOR

CONDITIONS OF APPROVAL, IF ANY:

DEC 1 1983