


Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico  
PlaceFebruary 27, 1952  
DateOIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Stanolind Oil & Gas Company  
Company or OperatorState TX

Lease

well No. 1 in EE/4of Sec. 32, T. 24, R. 38, N. M., P. M., Wildcat Field, Lea County.

N

The well is 1980 feet (N.) (S.) of the N line and 660 feet (W.) of the E line of Section 32

(Give location from section or other legal subdivision lines. Cross out wrong directions.)


If state land the oil and gas lease is No. 43520 Assignment No. \_\_\_\_\_

If patented land the owner is \_\_\_\_\_

Address \_\_\_\_\_

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is Stanolind Oil and Gas CompanyAddress Box 68, Hobbs, New MexicoWe propose to drill well with drilling equipment as follows: Rotary tools  
to total depth

AREA 640 ACRES

LOCATE WELL CORRECTLY

The status of a bond for this well in conformance with Rule 89 of the General Rules and Regulations of the Commission is as follows: \_\_\_\_\_

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17-1/2"	13-3/8"	36	New	300	Cemented	375 sk - circ.
12-1/4"	9-5/8"	32	New	4300	Cemented*	**
8-3/4"	7"	23	New	To be submitted later		

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 6300 feet.Additional information: \*To be two stage cemented with staging collar set at top of Salt approx 1300'. To isolate Salt Section from approx 1300 to 2600'.\*\* 1st stage, 300 sacks 8% gel plus 100 sacks neat. 2nd stage, 150 sacks neat.Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

Sincerely yours,

Stanolind Oil and Gas Company  
Company or OperatorBy Ralph L. HendricksonPosition Field Superintendent

Send communications regarding well to:

Name Ralph L. HendricksonAddress Box 68, Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Roy Yarrington

Title \_\_\_\_\_