

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

| | | | | | |
|---|--|---|-------------------------------------|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | <input checked="" type="checkbox"/> | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF PLUGGING WELL | | REPORT ON RECOMPLETION OPERATION | | REPORT ON (Other) | |

March 25, 1953 Hobbs, New Mexico
(Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company State Y
(Company or Operator) (Lease)
Davidson Drilling Company, Well No. 4 in the SW 1/4 NW 1/4 of Sec. 32
(Contractor)
T-24-S, R. 38-E, NMPM, West Dollarhide Pool, Lea County.

The Dates of this work were as follows: 3-22-53 to 3-24-53

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)
and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On March 22, 1953, ran 3567' of 5½" casing set at 3580' with staging tool set at 1232'. Cemented first stage with 100 sax 8% gel cement and 100 sax neat cement. Cemented second stage with 100 sax neat cement. After 12 hours temperature survey indicated top of cement at 1150.

After 30 hours tested DV tool with 1400 psi for 30 minutes with no drop in pressure. Drilled to float collar at 3483' and tested with 1150 psi for 30 minutes with no drop in pressure. Drilled shoe at 3580 and tested with 1400 psi for 30 minutes, no drop in pressure.

Since all tests were satisfactory drilling operations were resumed.

Witnessed by J. T. Crawford Stanolind Oil and Gas Company Head Roustabout
(Name) (Company) (Title)

Approved:

OIL CONSERVATION COMMISSION

Ray Yankovich
(Name)
(Title)
(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: *Ralph H. Hunsaker*
Position: Field Superintendent
Representing: Stanolind Oil and Gas Company
Address: Box 68, Hobbs, New Mexico