

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

RECEIVED

JUN 22 1953

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 16, 1953

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company

(Company or Operator)

State "NY" Lease

(Lease)

Loffland Brothers Company

(Contractor)

Well No. 6 in the NW 1/4 NW 1/4 of Sec. 32

T. 24-S, R. 38-E, NMPM., Undesignated Pool, Lea County.

The Dates of this work were as follows: June 14, 1953 to June 17, 1953 Inclusive.

Notice of intention to do the work (✓) (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_.

(Cross out incorrect words)

and approval of the proposed plan (✓) (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On June 14, 1953 ran 3138' of new 9-5/8" casing landed at 3149' and cemented with two stages with DV tool set at 1255.

1st Stage - cemented with 200 sacks neat cement.

2nd Stage - opened DV tool and circulated 6 hours and cemented with 150 sacks neat cement.

Temperature survey indicated top of cement at 1000'. After WOC 39 hours tested casing with 1000 psi for 30 minutes. Pressure dropped to 975 psi. Drilled DV tool and float at 3060 and tested with 1000 psi for 30 minutes. No drop in pressure. Drilled 96' of firm cement and shoe and tested with 1000 psi for 30 minutes and as there was no drop in pressure, drilling operations were resumed.

Witnessed by J. T. Crawford

(Name)

Stanolind Oil and Gas Company

(Company)

Head Roustabout

(Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: Ralph H. Hunsicker

Position: Field Superintendent

Representing: Stanolind Oil and Gas Company

Address: Box 68, Hobbs, New Mexico

*Roy J. Crawford*  
(Signature)  
Oil & Gas Inspector  
(Title)

JUN 22 1953

(Date)