

DEC 14 1953

OIL CONSERVATION COMMISSION
HOBBS-OFFICE

Santa Fe, New Mexico

WELL RECORD

AREA 640 ACRES
LOCATE WELL CORRECTLY

Stanelind Oil and Gas Company

.....
(Company or Operator)

State NYN

(Lease)

Well No. 7, in NW $\frac{1}{4}$ of NW $\frac{1}{4}$, of Sec. 32, T. 24-S, R. 36-E, NMPM.

Dollarhide - Queens

Pool 148

..County.

Well is 990' feet from North line and 660' feet from West line.

of Section 32 If State Land the Oil and Gas Lease No. is 9613

Drilling Commenced July 23, 1953, 19..... Drilling was Completed August 6, 1953, 19.....

Name of Drilling Contractor..... **Loffland Brothers Company**

Address P. O. Box 1649 - Tulsa, Oklahoma

Elevation above sea level at Top of Tubing Head.....**3162'**..... The information given is to be kept confidential until

Not Confidential

No. 1 from **3620** to **3775 (011)** No. 4 from.....to.....

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.

No. 2, from to feet.

No. 3, from.....to.....feet.

No. 4, from _____ to _____ feet. _____

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	29.35#	Used	299	Guide			Surface
5-1/2"	14#	New	3587	Float			Oil

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8"	310	150	Howee Plug		
7-7/8"	5-1/2"	3599	300	Howee Plug		

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sand Oil fractured with 20,000 gallons oil mixed with 10,000# sand.

Result of Production Stimulation.....**See Production on Reverse Side.**

..Depth Cleaned Out.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to TD 3775 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing August 16th, 1953
OIL WELL: The production during the first 24 hours was 90.67 barrels of liquid of which 99.9% was oil; % was emulsion; % water; and .1% was sediment. A.P.I. Gravity. 32° API
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1198		T. Devonian		T. Ojo Alamo
T. Salt			T. Silurian		T. Kirtland-Fruitland
B. Salt			T. Montoya		T. Farmington
T. Yates	2700		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen	3618		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres			T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn			T.		T.
T. Miss			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	310	310	Red Bed				
310	791	481	Red Bed and Shells				
791	1022	231	Red Bed				
1022	1302	280	Anhydrite and Shells				
1302	2556	1254	Anhydrite and Salt				
2556	2809	253	Anhydrite and Gyp				
2809	2887	78	Anhydrite				
2887	3005	118	Anhydrite and Gyp				
3005	3283	278	Anhydrite				
3283	3386	103	Lime				
3386	3461	75	Anhydrite and Lime				
3461	3706	245	Lime				
3706	3734	28	Sand				
3734	3758	24	Lime and Sand				
3758	3775	17	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

December 10, 1953

(Date)

Company or Operator Staholind Oil and Gas Company Address Box 68 - Hobbs, New Mexico
Name Ralph J. Pennington Position or Title Field Superintendent