

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)May 20, 1960
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Pan American Petroleum Corporation

State "N" Well No. 8 in 7 (Unit)
(Company or Operator) Lease
SE/ 1/4 NW/ 1/4 of Sec. 32, T. 24-S, R. 38-E, NMPM, Dollarhide Brinkard Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In effort to increase productivity of this well, the following is proposed:

1. Run Gamma Ray correlation log from 5800' to 6600'.
2. From correlation log perforate the following correlative zones from the electric log w/2 JSPP: 6317'-12', 6284'-73', 6262'-58', 6251'-45', 6219'-12', 6196'-89', & 6162'-55'.
3. Set retrievable bridge plug between 6330' & 6350' with tubing. Cap with 5' of sand. (Present perf. at 6364').
4. Spot 500 gal. of 15% reg. acid over perforations, then pull tubing up to 6100'.
5. Acid frase down the 2" J-55 tubing & the 5-1/2" 14# & 15.5# J-55 casing with 10,000 gal. of gelled acid with 10,000 lbs. of 20-40 mesh sand. Overflush with 10 barrels of oil.
6. Swab to test.

On Production Test 2-3-60 flw 39 BO O BW 24 hours.

Approved....., 19.....
Except as follows:

Pan American Petroleum Corporation

Original Signed by
Company or OperatorBy J. W. BrownPosition Area Superintendent

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSIONBy [Signature]Name J. W. Brown

Title.....

Address Box 68, Hobbs, New Mexico