NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well,

	Indicate Nature of Report by Che	cking Belo	W	
EPORT ON BEGINNING RILLING OPERATIONS	REPORT ON RESULT OF TE OF CASING SHUT-OFF	ST X	REPORT ON REPAIRING WELL	
EPORT ON RESULT F PLUGGING WELL	REPORT ON RECOMPLETIC OPERATION	N	REPORT ON (Other)	
		-54	Hobbs, N	Mexico
Following is a report on the work	done and the results obtained under tne	heading no	ted above at the	
Stanolind Oil and	Gas Company erator)		State WYW	·····
	orporation, Well No			
	larhide-Drinkard			
Dates of this work were as follows:	February 9, 1954, to 1	ebruar	y 11. 1954. inc	lusive
	V(rugs most) submissed on Form C 100 on			
	(was not) submitted on Form C-102 on	((Cross out incorrect words)	, 19
		((Cross out incorrect words)	, 19
d approval of the proposed plan ()	(was not) obtained. LED ACCOUNT OF WORK DONE AN	D RESULI	rs obtained	
On February 10, 19 cemented at 6627! hours W.O.C. teste and 1000 psi respections were re	(was not) obtained. LED ACCOUNT OF WORK DONE AN 54, 6612' of 5½" casing with 125 sx 4% gol plus d casing, before and as etively, for 30 minutes sumed.	vas r 125 c ter dr and s	rum im a 7-7/8" rum im a 7-7/8" ru. ft. perlite. rilling plug with as test was 0.K.	hole and After 32 h 1125 psi , completi
On February 10, 19 cemented at 6627! hours W.O.C. teste and 1000 psi respections were re	(was not) obtained. LED ACCOUNT OF WORK DONE AN 54, 6612' of 5½" casing with 125 sx 4% gol plus d casing, before and as etively, for 30 minutes sumed.	vas r 125 c ter dr and s	rs obtained Tun in a 7-7/8" Tun ft. perlite. Tilling plug with	hole and After 32 h 1125 psi , completi
On February 10, 19 cemented at 6627' hours W.O.C. teste and 1060 psi respe operations were re	(was not) obtained. LED ACCOUNT OF WORK DONE AN 54, 6612' of 5½" casing with 125 sx 4% gol plus d casing, before and at etively, for 30 minutes samed. Legeby Legeby	was related to the stand of the	rum im a 7-7/8" rum im a 7-7/8" ru. ft. perlite. rilling plug with as test was 0.K.	hole and After 32 h 1125 psi , completi
DETAI On February 10, 19 cemented at 6627! hours W.O.C. teste and 1000 psi respe- operations were re itnessed by J. T. Crawfor (Name)	(was not) obtained. LED ACCOUNT OF WORK DONE AN 54, 6612' of 5½" casing with 125 sx 4% gol plus d casing, before and at etively, for 30 minutes samed. Legeby Legeby	was related to the stand of the	run in a 7-7/8" run in a 7-7/	hole and After 32 h 1125 psi , completi
DETAI On February 10, 19 cemented at 6627! hours W.O.C. teste and 1000 psi respe operations were re	d	was related to the land sand Garage And Garage And Sand Sand Sand Sand Sand Sand Sand Sa	run in a 7-7/8" run in a 7-7/	hole and After 32 h 1125 psi h completi true and complete

(Date)

(Title)

Address Box 68, Hobbs, New Mexico