

[illegible]

Santa Fe, New Mexico

~~New Mexico~~
HUBBS OFFICE OCC

1951 MAY 25 AM 10:37
WELL RECORD

AREA 840 ACRES
LOCATE WELL CORRECTLY

Stanolind Oil and Gas Co.
(Company or Operator)

State "Y"
(Lease)

Well No. 11, in SE $\frac{1}{4}$ of NE $\frac{1}{4}$, of Sec. 32, T. 24-S, R. 38-E, NMPM.

~~Dollarhide-Drinkard~~ Pool, ~~Lea~~ County.

Well is 2310 feet from North line and 660' feet from East line

of Section 32 If State Land the Oil and Gas Lease No. is B-9613

Drilling Commenced 3-27-54, 1954 Drilling was Completed 5-2-54, 1954

Name of Drilling Contractor.....**Simmons Drilling Corp.**.....

Address Box 2322, Tulsa, Oklahoma

Elevation above sea level at Top of Tubing Head..... 3184' The information given is to be kept confidential until

Not Confidential..... 19.....

No. 1 from 6483 to 6492 No. 4, from 6573 to 6578

No. 2 from 6511 to 6537 No. 5, from 6597 to 6602

No. 3, from 6552 to 6557 No. 6, from 6682 to 6927

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet. _____

No. 2, from _____ to _____ feet. _____

No. 3, from to feet.

No. 4, from to feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13 3/8	36#	New	304'	Guide			
9 5/8	28-32#	New	3136'	Guide			
5 1/2	14-15.5#	New	6670'	Float			

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2	13 3/8	318	190	Howco Plug		
12 1/4	9 5/8	3150	350	Howco Plug		
7 7/8	5 1/2	6682	125-8%	Howco Plug		
			125 Cu. Ft.			

Perlite

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

8500 Gallons 15% Regular Acid

Result of Production Stimulation..... **See Reverse Side**

..Depth Cleaned Out

7 WORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 6927 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 5-1, 19 54

OIL WELL: The production during the first 24 hours was 133 barrels of liquid of which 100 % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity 40°

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta 5217	T.	T. Morrison
T. Drinkard 6168	T.	T. Penn
T. Tubbs	T.	T.
T. Abo 6654	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	318	318'	Caliche & Red Bed				
318	422	104	Red Bed				
422	804	382	Red Rock & Shale				
804	925	121	Red Bed				
925	1010	85	Red Rock				
1010	1335	325	Anhy.				
1335	1920	585	Anhy. & Salt				
1920	2295	375	Anhy-Gyp. & Salt				
2295	2595	300	Anhy - Salt				
2595	2667	72	Gyp.				
2667	3867	1200	Anhy. & Gyp.				
3867	4015	148	Lime				
4015	4037	22	Lime & Sand				
4037	4137	100	Lime				
4137	4316	179	Lime & Sand				
4316	6927	2611	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

May 21, 1954

(Date)

Company or Operator Stanolind Oil & Gas Co.

Address Box 68, Hobbs, New Mexico

Name Lucy R. Henderson

Position or Title Field Superintendent