

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Stanolind Oil and Gas Company

(Company or Operator)

State "N"

(Lease)

Well No. 14, in NE 1/4 of NW 1/4, of Sec. 32, T. 24-S, R. 38-E, NMPM.

Dollardhide-Queens

Pool, Lea

County.

Well is 990 feet from North line and 1650 feet from West line

of Section 32. If State Land the Oil and Gas Lease No. is B-9613

Drilling Commenced June 20, 1954. Drilling was Completed July 9, 1954

Name of Drilling Contractor Simmons Drilling Company

Address Box 2322, Tulsa, Oklahoma

Elevation above sea level at Top of Tubing Head 3187' RDB. The information given is to be kept confidential until

Not Confidential, 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
9"	34#	Used	288'	Guide			
5 1/2"	14#	New	3626'	Float			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/4	9"	302"	100	Howco Plug		
7-7/8	5 1/2"	3640	1st - 200 2nd - 100	Howco Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

20,000 gal. Sand-Oil Frac

Result of Production Stimulation See Reverse Side

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3812 feet, and from feet to feet.
 Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 7-8, 19.54
 OIL WELL: The production during the first 24 hours was 50 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity. 350
 GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
 Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1205		T. Devonian		T. Ojo Alamo
T. Salt			T. Silurian		T. Kirtland-Fruitland
B. Salt			T. Montoya		T. Farmington
T. Yates	2725		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen	3650		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres			T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn.
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn			T.		T.
T. Miss			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1260	1260	Red Bed				
1260	1270	10	Anhy.				
1270	2540	1270	Anhy. & Salt				
2540	2580	40	Salt & Gyp.				
2580	2642	62	Gyp.				
2642	3151	509	Anhy. & Gyp.				
3151	3553	402	Gyp. & Lime.				
3553	3689	136	Lime				
3689	3812	123	Lime & Sand				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

July 15, 1954 (Date)
 Company or Operator Stanolind Oil and Gas Company Address Box 68 - Hobbs, New Mexico
 Name Ruth Huie Position or Title Production Foreman