Form C-103

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten deve after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooring with the form commission of casing shut off, result of plugging of well, and other important operations, even though the work wet of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS	XX	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	-
REPORT ON RESULT OF PLUGGING OF WELL			

September 5, 1951 Hobbs, New Mexico Date Place

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporat	ion: H	arry Leonard	1	Well No. 7	in the
Compa	ny or Operator	L	ease		
SW SW		, T	2 4 5	, 38	, N. M. P. M.,
Not Designated		Lea			County.
The dates of this work were	as follows: 9-2-	51			
Notice of intention to do the	work Mark (was not) subr	nitted on Form C	C-102 on		, 19,

and approval of the proposed plan **F** (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Contractor moved in and spudded 17 1/2" hole at 7:00 p.m. 9-2-51.

Witnessed by	H. L. Campbell Name	Gulf Oil Corporation Company	Drilling Foreman Title
APPROVED: OIL CO	INSERVATION COMMISSION	is true and correct. Name	hat the information given above Japan . Supt.
	SEP 10 195	Representing	l Corporation ompany or Operator lobbs, New Merico

NE EXICO UIL CONS	FRVATION (O' SION
Submit this notice in triplicate to the Oil Conservation Com	
begin. A copy will be returned to the sender on which wi advisable, or the rejection by the Commission or agent, of t	an submission of its proper agent before the work specified is ill be given the approval, with any modifications (and the plan and the
and work should not begin until approval is obtained. Se	e additional instructions in the Rules and ROTHUGS
the Commission. Indicate nature of not	cice by checking below:
NOTICE OF INTENTION TO TEST CASING	NOTICE OF INTENTION TO SHOOT OR
SHUT-OFF 13 3/ NOTICE OF INTENTION TO CHANGE PLANS	CHEMICALLY TREAT WELL NOTICE OF INTENTION TO PULL OR
	OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	
Hot	bs New Maine Sautember 6 1951
	bbs, Now Les 100 Soutomber 6, 1951
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico	
Gentlemen:	
Following is a notice of intention to do certain work as des	cribed below at the
Gulf Oil Corporation Harry I	conard
Company or Operator Lease of Sec	N.M.P.M. Not Dogionated
LeaCounty.	
FULL DETAILS OF PRO	POSED DIAN OF WORK
FOLLOW INSTRUCTIONS IN THE RULES	AND REGULATIONS OF THE COMMISSION
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30	AND REGULATIONS OF THE COMMISSION
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated.	AND REGULATIONS OF THE COMMISSION ats, 291', of 13 3/8" OD 8 R.T. 48# 06' with 325 sacks regular bulk
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated.	AND REGULATIONS OF THE COMMISSION Ats, 291', of 13 3/8" OD 8 R.T. 48# 06' with 325 sacks regular bulk Job complete at 11:15 a.m. 9-3-51.
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated.	AND REGULATIONS OF THE COMMISSION ats, 291', of 13 3/8" OD 8 R.T. 48# 06' with 325 sacks regular bulk Job complete at 11:15 a.m. 9-3-51.
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated. Propose to drill plug and test ca	AND REGULATIONS OF THE COMMISSION ats, 291', of 13 3/8" OD 8 R.T. 48# O6' with 325 sacks regular bulk Job complete at 11:15 a.m. 9-3-51. Asing shut-off at 11:15 p.m. 9-5-51.
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated.	AND REGULATIONS OF THE COMMISSION ats, 291', of 13 3/8" OD 8 R.T. 48# O6' with 325 sacks regular bulk Job complete at 11:15 a.m. 9-3-51. Asing shut-off at 11:15 p.m. 9-5-51.
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated. Propose to drill plug and test ca	AND REGULATIONS OF THE COMMISSION ats, 291', of 13 3/8" OD 8 R.T. 48# O6' with 325 sacks regular bulk Job complete at 11:15 a.m. 9-3-51. Asing shut-off at 11:15 p.m. 9-5-51.
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated. Propose to drill plug and test ca	AND REGULATIONS OF THE COMMISSION Ats, 291', of 13 3/8" OD 8 R.T. 48# 26' with 325 sacks regular bulk Job complete at 11:15 a.m. 9-3-51. Asing shut-off at 11:15
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated. Propose to drill plug and test ca ApprovedSEP_10.195119 except at follows: OIL CONSERVATION COMMISSION,	AND REGULATIONS OF THE COMMISSION And REGULATIONS OF THE COMMISSION Ats, 291', of 13 3/8" OD 8 R.T. 48# 26' with 325 macks regular bulk Job complete at 11:15 a.m. 9-3-51. Asing shut-off at 11:15 a.m. 9-5-51. Asing shut-off at 11:15 a.m. 9-5-51. By Company or Operator By Company or Oper
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated. Propose to drill plug and test ca Propose to drill plug and test ca spprovedSEP_1.0.1951	AND REGULATIONS OF THE COMMISSION Ats, 291', of 13 3/8" OD 8 R.T. 48# 26' with 325 sacks regular bulk Job complete at 11:15 a.m. 9-3-51. Asing shut-off at 11:15 p.m. 9-5-51. Asing shut-off at 11:15 p.m. 9-5-51. By Company or Operator By Co
On September 3, 1951, ran 10 join H-40 new SS casing, set and cemented at 30 cement. Plug at 296'. Cement circulated. Propose to drill plug and test ca	AND REGULATIONS OF THE COMMISSION And REGULATIONS OF THE COMMISSION Ats, 291', of 13 3/8" OD 8 R.T. 48# 26' with 325 macks regular bulk Job complete at 11:15 a.m. 9-3-51. Asing shut-off at 11:15 a.m. 9-5-51. Asing shut-off at 11:15 a.m. 9-5-51. By Company or Operator By Company or Oper