

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	27197

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
Gulf Oil Corporation	
3. Address of Operator	9. Well No.
Box 670, Hobbs, New Mexico 88240	106
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER <u>K</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>781</u> FEET FROM	Dollarhide Devonian
THE <u>East</u> LINE, SECTION <u>33</u> TOWNSHIP <u>24-S</u> RANGE <u>38-E</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3173' GL	Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
		OTHER <input type="checkbox"/>	

Plugged and abandoned

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7995' PB, 8025' TD.

Ran CI cement retainer and set at 3900'. Squeezed with 1000 sacks of Class C cement containing .75% CFR-2 and 8# salt per sack. Maximum pressure 800#. ISIP 0#. WOC 12 hours. TS indicated TOC outside 7" casing at 1115'. Loaded hole with 14.2# mud. Spotted cement plug from 50' to surface. Installed dry hole marker. Plugged and abandoned August 19, 1973. (Will advise when location is ready for inspection).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. J. Breazeal TITLE Area Engineer DATE August 22, 1973

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: