

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

MISCELLANEOUS NOTICES

JUL 31 10 02 AM '64

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <u>Test San Andres</u>	X	NOTICE OF INTENTION (OTHER)	

for a water supply source.

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Kermit, Texas
(Place)

7-30-64
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Gulf Oil Corporation

West Dollarhide Devonian Unit Well No. 33-14 in N
(Company or Operator) (Unit)

SE $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. 33, T. 24-S, R. 38-E NMPM, Dollarhide Devonian Pool
(40-acre Subdivision) Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to set CI bridge plug at 5300', cap with cement, perforate with 2 holes immediately above plug. Run magnesium retainer on tubing, set above perforations and circulate 200 sacks cement with 4% gel behind 7" casing. Run temperature Survey and GR-N log, perforate San Andres. Run 2- $\frac{1}{2}$ " tbg. Acidize San Andres with 5000 gal. Swab test. If a large volume of water is obtained, rent Reda equipment and test. After completion of all testing in San Andres, run magnesium retainer on tubing and set above San Andres perforations, squeeze perforations, drill out cement with reverse equipment to bridge plug at 5300', pressure test perforations with 1000 psig, drill out bridge plug. Run injection equipment and return to injection service.

Approved _____, 19____
Except as follows:

Approved _____
OIL CONSERVATION COMMISSION

By _____
Title _____

Gulf Oil Corporation

Company or Operator

By _____

Position Area Production Manager

Send Communications regarding well to:

Name Gulf Oil Corporation

Address P. O. Box 980, Kermit, Texas