

TRIPPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work reported is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

May 25, 1953
(Date)

Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation
(Company or Operator)

Harry Leonard "A"
(Lease)

Wood Drilling Company
(Contractor)

Well No. 26 in the SE 1/4 NW 1/4 of Sec. 33

T. 24-S., R. 38-E., NMPM., Dollarhide West Drinkard Pool, Lea County.

The Dates of this work were as follows: May 21-23, 1953

Notice of intention to do the work (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)

and approval of the proposed plan (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 152 Jts. 6269' of 7" OD 23# N-80 and J-55 SS Casing. Set and cemented at 6279' with 2 stages. Bottom stage 900 sacks 4% Gel and 100 sacks Neat on bottom. Left 300' cement in casing. Pressure 2600#. Second stage through DV tool at 1199' with 325 sacks 4% Gel cement. Maximum pressure 500#. By HOWCO. Gulf Temp. survey after 8 hrs. indicated top cement behind 7" casing at 297' below DP.

After waiting over 48 hrs. tested 7" casing w/1000# for 30 min. No drop in pressure. Drilled plug in HOWCO DV tool at 1199' and tested DV tool w/1500# for 30 min., no drop in pressure. Drilled cement to 6279', tested cement below casing shoe w/800# for 30 min. No drop in pressure.

After approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to complete well.

Witnessed by R. S. Ruyon
(Name)

Gulf Oil Corporation
(Company)

Drilling Foreman
(Title)

Approved: OIL CONSERVATION COMMISSION

Roy Yarbrough
(Name)
(Title)
(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name R. S. Ruyon
Position Asst. Area Prod. Supt.
Representing Gulf Oil Corporation
Address Box 2167, Hobbs, New Mexico