

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form O-103
Revised 10-1-77

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM O-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- <u>INJECTION WELL</u>	3. Indicate Type of Lease State ☒ Fee ☐
2. Name of Operator <u>TEXACO PRODUCING INC</u>	5. State Oil & Gas Lease No. <u>B-1732</u>
2. Address of Operator <u>P.O. BOX 728, HOBBS, NEW MEXICO 88240</u>	7. Unit Agreement Name <u>WEST DOLLARHIDE DRINKARD UNIT</u>
3. Location of Well UNIT LETTER <u>D</u> <u>990</u> FEET FROM THE <u>NORTH</u> LINE AND <u>990</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>33</u> TOWNSHIP <u>24-S</u> RANGE <u>38-E</u> NADPH.	8. Farm or Lease Name
15. Elevation (Show whether DF, RT, GR, etc.) <u>3207 D.F.</u>	9. Well No. <u>41</u>
	10. Field and Pool, or Wellcut <u>DOLLARHIDE TUBB DRINKARD</u>
	12. County <u>LEA</u>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- ON OCTOBER 27, 1988. MIRU. INSTALLED BOP GIH w/WORKSTRING. TAGGED CIBP @ 4300'
- CIRCULATED HOLE w/9.5 LB GELLED BRINE. SPOTTED 50SX CLASS C CEMENT WITH 2% CaCl₂ ON TOP OF CIBP, FROM 4300' TO 4000'.
- POH AND SPOTTED 50SX CLASS C CEMENT FROM 3570' TO 3273' TOH.
- RIG UP WIRELINE COMPANY. CUT-OFF 7" CSG AT 2043'. PULLED 50 JTS CF 7" CSG. RIG DOWN WIRELINE.
- TIH w/WORKSTRING. SPOTTED 40SX CLASS C CEMENT FROM 2950' - 2700'.
- POH AND SPOTTED 50SX CLASS C CEMENT FROM 2100' TO 1900'.
- POH AND SPOTTED 35SX CLASS C CEMENT FROM 1230' TO 1130'.
- POH AND SPOTTED 35SX CLASS C CEMENT FROM 377' TO 277'.
- POH AND SPOTTED 30 FT SURFACE PLUG.
- RIG DOWN. INSTALLED DRY HOLE MARKER.

EFFECTIVE NOVEMBER 1, 1988 WEST DOLLARHIDE DRINKARD UNIT WELL NO. 41
WELL STATUS CHANGED FROM T.A. TO P&A.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED K. E. Johnson TITLE AREA SUPERINTENDENT DATE NOV 14 1988

APPROVED BY Lytle F. Tammcliff TITLE OIL & GAS INSPECTOR DATE DEC 27 1988

CONDITIONS OF APPROVAL, IF ANY: