

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
B-1732

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- INJECTION WELL	7. Unit Agreement Name WEST DOLLARHIDE DRINKARD UNIT
2. Name of Operator TEXACO PRODUCING INC	8. Farm or Lease Name
3. Address of Operator P.O. BOX 728, HOBBS, NEW MEXICO 88240	9. Well No. 41
4. Location of Well UNIT LETTER D 990 FEET FROM THE NORTH LINE AND 990 FEET FROM THE WEST LINE, SECTION 33 TOWNSHIP 24S RANGE 38E N.M.P.M.	10. Field and Pool, or Wildcat DOLLARHIDE TUBB DRINKARD
11. Elevation (Show whether DF, RT, GR, etc.) 3207' D.F.	12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. MIRU. INSTALL BOP.

2. GIH w/ WORKSTRING. CIRC. HOLE FULL OF 9.5 LB PER GAL MUD.

3. SPOT 50 SX CLASS C CEMENT (298 FT PLUG) 4000'-4300', WITH 2% CaCl₂ ON TOP OF EZ-DRILL CEMENT RETAINER AT 4300.

4. POH AND SPOT 50 SX CLASS C CEMENT (298 FT PLUG) 3270'-3570', ABOVE THE DOLLARHIDE QUEEN (3570) ZONE. TOH.

5. RUN CASING- FREE POINT. CHEMICALLY CUT 7" CSG AT 2845' (TOC AS PER TEMPERATURE SURVEY- 1953 DRILLING REPORT).

6. PULL 7" CSG.

7. GIH AND SPOT 50 SX CLASS C CEMENT (100 FT PLUG) 2850'-2950', ACROSS 9 5/8" CSG SHO-.

8. POH AND SPOT 50 SX CLASS C CEMENT (100 FT PLUG) 1130'-1230', ACROSS TOP OF SALT (1230).

9. POH AND SPOT 35 SX CLASS C CEMENT (100 FT PLUG) 277'-377'.

10. POH AND SPOT 4 SX CLASS C CEMENT (10 FT PLUG) AT SURFACE.

11. RIG DOWN. INSTALL DRY HOLE MARKER AND CLEAN LOCATION.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED K. Johnson TITLE AREA SUPERINTENDENT DATE SEP 28 1993
ORIGINAL SIGNED BY TERREY SEXTON
APPROVED BY LEA TITLE LEA DATE SEP 28 1993
CONDITIONS OF APPROVAL, IF ANY: