

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED

JUL 24 1953

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after completion of the work. This report should be completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	XX	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

July 24, 1953  
(Date)

Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation  
(Company or Operator)

Harry Leonard "A"  
(Lease)

Gardner Bros. Drilling Co.  
(Contractor)

28 in the 1/4 of Sec. 33

T. 24-S., R. 32-E., NMPM, Dollarhide-Most Driftwood Pool, Lea County.

The Dates of this work were as follows: July 17 to 20, 1953

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_,  
(Cross out incorrect words)

and approval of the proposed plan ~~(was)~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 190 Jts (6943.71') of 7" 3 Rnd Tnd 23# H-80 and J-55 Casing with 9 Weatherford Centralizers from 6950-6290' and 50 Weatherford Scratchers from 6956-6300'. Set and cemented at 6959' with 750 sacks 45 Gel Lone Star cement. Plug at 6876'. Max. Pressure 1700#. Job completed by Howco at 10:00 AM 18th. Gulf Temperature survey after 12 hours showed top of cement at 2945'.

After waiting over 36 hours, tested 7" casing with 1000# for 30 minutes, there was no drop in pressure. Drilled plug and cement from 6873-6945' and tested cement below casing shoe with 1000# for 30 minutes, there was no drop in pressure.

After approval of Mr. Yarbrough, State Oil & Gas Inspector, preparations were made to complete the well.

Witnessed by \_\_\_\_\_  
(Name)

Gulf Oil Corporation  
(Company)

Drilling Foreman  
(Title)

Approved: OIL CONSERVATION COMMISSION

Roy Yarbrough  
(Name)  
(Title)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name \_\_\_\_\_  
Position \_\_\_\_\_  
Representing \_\_\_\_\_  
Address \_\_\_\_\_

JUL 27 1953  
(Date)