

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

May 27, 1953  
(Date)Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation

(Company or Operator)

Harry Leonard "A"

(Lease)

Gardner Bros. Drilling Co.

(Contractor)

Well No. 28 in the NW 1/4 NW 1/4 of Sec. 33

T. 24-S., R. 38-E., NMPM., Dollarhide-West Devonian Pool, Lea County.

The Dates of this work were as follows: May 22-23, 1953

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_,  
(Cross out incorrect words)and approval of the proposed plan (~~was~~) (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 89 jts. 2888' of 9-5/8" OD 36 & 32.30# J-55 & H-40 SS Casing ~~2903'~~ Howco DV tool at 1280'. Set & cemented at 2903' in two stages. 1st stage 2/200 sx 4% Gel & 100 sx Neat cement, Max. Press. 700#, 2nd stage thru DV tool at 1280' w/550 sx 4% Gel. Max. Press. 500#. Circ. 40 sx cement.

After waiting over 24 hrs. tested 9-5/8" csg. & BOP w/1500# for 30 min, no drop in pressure. Drilled plug in Howco DV tool at 1280', tested DV tool w/1500# for 30 min, no drop in pressure. Drilled cement to 2903' tested cement below csg shoe w/1000# for 30 min, no drop in pressure.

After approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to drill ahead.

Witnessed by C. E. Langford  
(Name)Gulf Oil Corporation  
(Company)Drilling Foreman  
(Title)

Approved:

OIL CONSERVATION COMMISSION

*Ray Yarbrough*  
(Signature)  
(Title)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name *W. B. Sherron*

Position Asst. Area Prod. Supt.

Representing Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico