

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

RECEIVED
JUL 14 1953
COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

July 13, 1953 Hobbs, New Mexico
(Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation Harry Leonard "A"
(Company or Operator) (Lease)

Wood Drilling Co., Well No. 30 in the NE 1/4 SW 1/4 of Sec. 33
(Contractor)

T. 24-S., R. 38-E., NMPM., Dollarhide West Drinkard Pool, Lea County.

The Dates of this work were as follows: July 9-11, 1953

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 153 jts 6287' 7" OD 8 RT 23# H-80 & J-55 SS casing w/14 leather ord scratchers & 3 weatherford centralizers from 6139' to 6195'. Set & cemented at 6299' w/1171 sacks cement in 2 stages. 1st stage w/626 sacks Reg 4% Gel cement & 150 sacks Neat on bottom. Max. press. 1000#. 2nd stage thru Howco DV tool at 1265' w/345 sacks reg 4% Gel cement & 50 sacks Neat on bottom.

After waiting over 36 hrs. tested 7" casing w/1000# for 30 min, no drop in pressure. Drilled plug in Howco DV tool at 1264' and tested DV tool w/2500# for 30 min, no drop in pressure. Went in hole to top cement plug 6230' and drilled cement to 6300'. Tested cement below casing shoe w/1000# for 30 min. No drop in pressure.

After approval of Mr. Yarbrough, State Oil & Gas Inspector, preparations were made to complete well.

Witnessed by J. F. Combs Gulf Oil Corporation Drilling Bremen
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

Ray Yarbrough
(Name)
State Oil & Gas Inspector
(Title)

JUL 14 1953
(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name _____
Position Asst. Area Prod. Supt.
Representing Gulf Oil Corporation
Address Box 2167, Hobbs, New Mexico