

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Texaco Exploration & Production Inc.

3. Address and Telephone No.

P.O. Box 730, Hobbs, NM 88241-0730 (505) 393-7191

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter A, 990 FNL, 940 FEL,  
Section 24, T-25-S, R-37-E

5. Lease Designation and Serial No.

LC - 032650b

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

A.B. Coates C #25

9. API Well No.

30 - 025 - 20060

10. Field and Pool, or Exploratory Area

South Justis BL, TD

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

(see other side)

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Engineer

Date 1-13-93

(This space for Federal or State office use)

Approved by  
Conditions of approval, if any:

Title

Date 1-21-93

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

# DASS OIL WELL SERVICING

INCORPORATED

TEXACO EXPLORATION & PRODUCTION  
A. B. COATES "C" FEDERAL - #25

- 12/14/92 - MOVE IN, RIG UP, INSTALL B.O.P., PICK UP 2 1/16" TUBING IN BLINEBRY SIDE, TAG AT 1100' WITH BIT AND SCRAPER, PULL OUT. RUN IN DRINKARD SIDE, TAG AT 1600' WITH BIT AND SCRAPER. RUN IN BLINEBRY OPEN-ENDED, TAG AT 1136', PULL OUT. RUN IN DRINKARD OPEN-ENDED, TAG AT 1621', PULL OUT, SHUT DOWN.
- 12/15/92 - PICK UP ON DRINKARD SIDE, TUBING PARTED, RUN TUBING IN, DRINKARD SIDE, CIRCULATE WELL BACK INTO CELLAR, DIG OUT CELLAR, 9 5/8" SURFACE PIPE IN, TO 5' FROM SURFACE, CHIP OUT CEMENT, GET READY TO PATCH 9 5/8" PIPE, SHUT DOWN.
- 12/16/92 - PULL 2 7/8" CASING FROM DRINKARD SIDE, 34 JOINTS 1.029, CIRCULATE WELL WITH MUD, WELD PATCH ON 9 5/8" CASING, FILL CELLAR WITH CEMENT, SHUT DOWN.
- 12/17/92 - REMOVE B.O.P., PULL 2 7/8" CASING, BLINEBRY SIDE PARTED AT 1098', INSTALL B.O.P., RUN 7" FISHING TOOL TO FISH 2 7/8" COLLAR ON DRINKARD SIDE, GET FISH, PULL 8 POINTS, SET ON SLIPS, GET READY TO RUN 2 5/16" MILL ON 1 5/8" DRILLPIPE IN DRINKARD SIDE, SHUT DOWN.
- 12/18/92 - RUN 1 5/8" DRILLPIPE AND MILL, TAG AT 1030', DRILL OUT TO 3500', SHUT DOWN.
- 12/19/92 - DRILL FROM 3500'-5077', PULL OUT OF HOLE, SHUT DOWN.
- 12/21/92 - RUN CEMENT RETAINER ON WIRELINE, SET AT 5000', RUN 1 5/8" DRILLPIPE WITH STINGER, CIRCULATE MUD, STING INTO CEMENT RETAINER, PUMP 31 SACKS OF CEMENT UNDER RETAINER, PRESSURE 1800, SPOT 10 SACKS OF CEMENT ON TOP OF RETAINER, PULL TUBING TO 2435', SPOT 15 SACKS OF CEMENT, PULL TUBING, SHUT DOWN.
- 12/22/92 - RUN TUBING CUTTER ON WIRELINE, TAG CEMENT AT 1700', CUT 2 7/8" CASING AT 1600' DRINKARD SIDE, PULL OUT CASING, RUN IN HOLE WITH 7" FISHING TOOL ON 2 7/8" TUBING, FISH BLINEBRY SIDE, 1098', RUN 2 5/16" MILL ON 1 5/8" DRILLPIPE, DRILL FROM 1098'-1230', SHUT DOWN.
- 12/23/92 - PULL TUBING, CHANGE OUT, MILL BACK IN HOLE, DRILL FROM 1230'-1465', PULL PIPE, SHUT DOWN.
- 12/28/92 - RUN 2 5/16" MILL AND 1 5/8" DRILLPIPE, TAG AT 1465', DRILL OUT TO 1919', PULL OUT OF HOLE, SHUT DOWN.

505-392-6591 • P.O. BOX 2545 • HOBBS, NEW MEXICO 88241

HOBBS, NEW MEXICO 505/ 392-6591  
ANDREWS, TEXAS 815/ 523-4420

LOCATIONS

ELINCE, NEW MEXICO 505/ 394-6267  
MOLAND, TEXAS 815/ 665-9555

- 12/29/92 - RUN PIPE IN HOLE, TAG AT 1919', DRILL DOWN TO 4924', PULL PIPE OUT, RUN CAST IRON BRIDGE PLUG, 2 7/8" ON WIRELINE, SET AT 4898', SHUT DOWN.
- 12/30/92 - RUN 1 5/8" DRILLPIPE, TAG CAST IRON BRIDGE PLUG AT 4898', CIRCULATE MUD, SPOT 5 SACKS OF CEMENT FROM 4898'-4685', PULL TUBING TO 2435', SPOT 16 SACKS OF CEMENT FROM 2435'-1650', PULL TUBING OUT, RUN 2 1/8" TUBING, CUTTER ON WIRELINE, CUT 2 7/8" CASING AT 1600', PULL AND LAY DOWN 2 7/8" BLINEBRY SIDE, RUN 2 7/8" TUBING IN HOLE, CIRCULATE MUD, SPOT 50 SACKS OF CEMENT FROM 1600'-UP HOLE, PULL TUBING, SHUT DOWN.
- 12/31/92 - TAG CEMENT AT 1573', PLUG FROM 1600'-1573', SPOT 150 SACKS OF CEMENT FROM 1573'-UP HOLE, WAIT ON CEMENT, TAG CEMENT AT 1432', CEMENT FROM 1573'-1432', PLUG FROM 1600'-1432', PULL TUBING TO 943', SPOT 70 SACKS OF CEMENT FROM 943'-UP, PULL TUBING OUT, SHUT DOWN.
- 01/04/93 - TAG CEMENT AT 801', PLUG FROM 943'-801', PULL TUBING TO 100', FROM SURFACE, CIRCULATE 40 SACKS OF CEMENT TO SURFACE, PULL TUBING OUT, CUT OFF WELLHEAD, INSTALL MARKER, FILL CASING AND CELLAR WITH CEMENT, RIG DOWN, MOVE OFF.