



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

1963 JAN 10 AM 9:50

Land Office **Las Cruces**
Lease No. **032650 (b)**
Unit **A. B. Coates "C"**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 18

1963

Well No. **25** is located **990** ft. from **(N)** line and **940** ft. from **(E)** line of sec. **24**
NE/4, Sec. 24 **25S** **37E** **NMPM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Justis Blinbry-Tubb-Drinkard Lea **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Spudded 4:30 P.M., 1-11-63. Drilled 12-1/4" hole to 900'. Set 9-5/8" 36# J-55 casing at 893'. Cemented w/ 346 sks. reg. 50-50 Diamix w/ 4% gel & 100 sks. Neat w/ 1/4# floccle/sk. Cement circulated, but fell after job completed. Found cement 20' from surface. Recemented w/ 10 sk. WOC 24 hours, tested casing w/ 1100# for 30 mins., no drop in pressure.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Tidewater Oil Company**

Address **Box 547**

Hobbs, New Mexico

By **A. J. White**

Title **Area Supt.**