

Submit 3 Copies To Appropriate District Office

District I  
1625 N. French Dr., Hobbs, NM 87240

District II  
811 South First, Artesia, NM 87210

District III  
1000 Rio Brazos Rd., Aztec, NM 87410

District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator HENRY PETROLEUM LP

3. Address of Operator 3525 ANDREWS HIGHWAY - SUITE 200 - MIDLAND TX  
79703-5000

4. Well Location  
Unit Letter C 660 feet from the NORTH line and 2310 feet from the WEST line  
Section 23 Township 25-S Range 37-E NMPM LEA County NEW MEXICO

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3090.8 GR

WELL API NO. 30-025-20081

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
SOUTH JUSTIS UNIT

8. Well No. -B- #19

9. Pool name or Wildcat  
JUSTIS-BLBRY-TUBB-DRINKARD

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:  
PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: ☐  
SUBSEQUENT REPORT OF:  
REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion.

- 1) PULL OUT OF HOLE W/DOWNHOLE PRODUCTION EQUIPMENT.
- 2) RUN IN HOLE W/CIBP AND SET ABOVE PRODUCING INTERVAL (TOP PERF. AT 5167').
- 3) TRIP IN HOLE W/RBP & PACKER & LOCATE LEAK - ESTIMATED TO BE AT 4100'.
- 4) PULL OUT OF HOLE WITH PACKER & PLUG.
- 5) SQUEEZE CASING LEAK BELOW CEMENT RETAINER.
- 6) DRILL OUT RETAINER & CEMENT.
- 7) LOAD HOLE & PRESSURE TEST TO 500 PSI.
- 8) KNOCK OUT CIBP & RETURN WELL TO PRODUCTION.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy R. Johnson TITLE REGULATORY TECH. DATE 09/07/2001

Type or print name ROY R. JOHNSON

(This space for State use)

APPROVED BY

TITLE

DATE

Conditions of approval, if any:

