

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

- | | |
|---|--|
| 1. OIL ☒ GAS ☐
WELL WELL OTHER | 7. UNIT AGREEMENT NAME |
| 2. NAME OF OPERATOR
The Atlantic Refining Company | 8. FARM OR LEASE NAME
Gregory |
| 3. ADDRESS OF OPERATOR
P.O. Box 1978, Cornwall, N.Y. | 9. WELL NO.
1 |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
2310' L, 130' W | 10. FIELD AND POOL OR WILDCAT
Justis - Flinetry |
| 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. 35, 7-25, 4-30 | 12. COUNTY OR PARISH
La |
| 13. STATE
N.Y. | 14. PERMIT NO. |
| 15. ELEVATIONS (Show whether DE, RT, GR, etc.)
237' | |
| 16. Check Appropriate Box To Indicate Nature of Notice. Report, or Other Data | |

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO :

SUBSEQUENT REPORT OF :

TEST WATER SHUT-OFF

BEFORE OR AFTER CASTING

WATER SURFACES

REPAIRING WELL.

FRAC: RE: TRSM

EXEMPLE COMPLET

FRACURE TREATMENT

ALTERING CASING

SHORT OR ABUSE?

ABANDON

SHO TUNG CHEN & JIZHONG

ABANDONMENT*

E. J. P. VAN DER MEULEN

CHANGE CLASS

• 409 •

Year	1990	1995	2000	2005	2010
Population (millions)	1.2	1.4	1.6	1.8	2.0
GDP (billions of dollars)	0.5	1.0	1.5	2.0	2.5
Life expectancy (years)	55	60	65	70	75

$$= O(h_1 + r)$$

(Normal: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. ESSENTIAL PROPOSED OR PLANNED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measures, and true vertical depths for all markers and zones pertinent to this work.)⁸

Rigged 7-7/8" hole to 5206' T.S. - Under pressure - 1400 psi, 140° Colog., Micro-
-annular sealable bit. Set 180 lbs of cement at 5206' - 5210.5' - 95 #13 casing,
float collar and float shoe = 5762.2'. Set at 5210.5' - 5215' - Cemented 1/326 sx
liner plus 8' gal and 10' liner seat. Liner set at 5215' - 5218.1/2/62. Top of cement
at 3090' by temperature survey. Well shut hours. Cement 1-1/2" casing w/10# brine
water to 1800' for 30 minutes. Then get complete log down to 1/23/62. Perforated
slimwall, 5217-78 and 5220-92' (10' w/10#). Total 1000 gallons mud acid and
500 gallons 1" L.H.B., 10,000 gallons base crude oil, 10,000 20/40 sand.
Set 11-3/4" packer and 100 lbs 2-1/2" 100 J-51 sand for completion. Logging
bottomed at 5218.62'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE January 31, 1964

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.