

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 01995

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Langlie "D"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Justis Blinebry

11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA

Sec 14, T-25-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR

1300 Wilco Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)

At surface

1650' FSL & 2310' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3117 DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Also-Squeeze old perfs.

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Re-enter well and pull 2-3/8" tubing.

2. Set Bridge plug at 5195' and squeezed old perfs at 5182' and 5188'.

3. Drill out bridge plug and any cement in casing.

4. Reperforate any interval below 5200' in which cement was drilled.

5. Stimulate as necessary and frac with 80,000 gal. jelled water + 12,000<sup>22</sup> 20/40 sand in stages using blocking agent and temperature surveys for control.

6. Run rods and pump and place well on production.

18. I hereby certify that the foregoing is true and correct

SIGNED Stanley A. Post

TITLE Gas Measurement Analyst

DATE October 9, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

**APPROVED**  
OCT 11 1974

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side