

B3 Well No. 3

DATE: 5-17-64

Present Wellbore

size 2 7/8
wt. 6.4"
grade J-55
set @ 6243
hole size 7 5/8
cement 900 SX
cml. top @ 2600' (temp. survey)

SIZE: 11 3/4

WEIGHT: 23.72

GRADE: 11 1/2

SET @: 249

HOLE SIZE: 15

CEMENT: 350 SX

cml. circ.

SIZE: 8 1/2

WEIGHT: 24

GRADE: J-55

SET @: 2500

HOLE SIZE: 10 5/8

CEMENT: 850 SX

cml. top @ 1800' (temp. survey)

size 2 7/8
wt. 6.4"
grade J-55
set @ 6244
hole sz 7 5/8
cement 900 SX
cml. top @ 2600' (temp. survey)

Top 5192
Blindbry
P.S (9-71) 5192-97 (135FF), 5221, 22, 24, 29, 31, 34, 36, 39,
w/135FF, 5249-52 w/135FF
P.S (1-70) 5273-79 (135FF), 5281, 82, 5308, 12, (135FF),
5321-24 (135FF), 5352, 98, 99, 5416, 18, 63, 64, (135FF)
5422-45, 5523-25 (135FF), 5555, 59 (135FF)
P.S (2-65) 5421, 23, 26, 86, 5535, 49, 57, 66, 70, 81, 5505 (135FF)
P.S (2-63) 5444, 66, 78, 91 (135FF)

(3-84) Pap anchor & bottom & p.p. cage @ 5500'
(12-63) Pap anchor LIH @ 5505
Communications Sound 5567-5620 (9-71)
DHC PerS (5-74) 5551-661

Bottom 5691

RA collar @ 5605'

5713' CIBP set (9-71)
Fish LIH (9-71), 8-5/8 rods & pump
Top @ 5750'

Justis Tubb Drinkard Top 5883

5-14-74 Tapped TD at 6016'
Possibly frac sand & ball sealers

PerS (9-65) 6008, 11, 21, 37, 52, 65 w/135FF
PerS (8-63) 6007, 103, 115, 124, 133, 134, 147 w/135FF

Bottom 6127

TD 6249

PERF = 6204'

PERF = 6211'

RECEIVED

AUG 17 1984

U.S. DEPT.
HOMELAND SECURITY