NOTICE OF INTENTION TO DRILL	SUBSPOUENT REPORT OF WATER COMP.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.	or Shooting or Acidizing.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	STATE OF ALTERNING CASING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	OF REPAIR
	SUBSEQUENT REPORT OF ABANDONMENT. SUPPLEMENTARY WELL HISTORY.
NOTICE OF INTENTION TO ABANDON WELL.	OUT CEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK MARK	(NATURE OF REPORT, NOTICE, OR OTHER DATA)
ease No. 41696	-i -:
. L. Erwin "a"	Annil O
	April 9 , 196
W/4 SW/4 Sec. 35 T-24-S R (K Sec. and Sec. No.) (Twp.)	line and 990 ft. from $\{W\}$ line of sec. 35. $R-37-E$ NMPM
(Twp.)	(Range) (Meridian)
ustis N. (Blinebry) Lea ustis N. (Tubb-Drinkard) (County or	New Mexico
ustis N. (Tubb-Drinkard) (County or	r Subdivision) (State or Territory)
he elevation of the derrick floor above sea leve	elic * fr * Not Arrodloble
The second secon	
	cis
DETAIL	LS OF WORK
DETAIL	LS OF WORK
DETAIL	
DETAIL sate names of and expected depths to objective sands; show sizes ing points, and all ot	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cement her important proposed work)
DETAIL tate names of and expected depths to objective sands; show sizes ing points, and all oti TD 3 50 ° of 11-3/4" OD casing set as	LS OF WORK 15, weights, and lengths of proposed casings; indicate mudding jobs, cement the important proposed work) 15451 1. 2641
DETAIL tate names of and expected depths to objective sands; show sizes ing points, and all other states of the s	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer 1545! t 264! et at 3545! DV tool at 2505!
DETAIL tate names of and expected depths to objective sands; show sizes ing points, and all oil TD 3 50 of 11-3/4" OD casing set a an 3534 of 8-5/8" OD casing seement first string with 400 sages	LS OF WORK a, weights, and lengths of proposed casings; indicate mudding jobs, cemer 3545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plus at
DETAIL tate names of and expected depths to objective sands; show sizes ing points, and all of the sands of	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stages comented
DETAIL tate names of and expected depths to objective sands; show sizes ing points, and all of the sands of	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stages comented
DETAIL tate names of and expected depths to objective sands; show sizes ing points, and all oil TD 3 50' of 11-3/4" OD casing set at an 3534' of 8-5/8" OD casing seement first string with 400 sates and 130'. Circulate 4 hours between the 1300 sacks of TLW plus 100 and 100 plus 100 plus 100 plus 4-7-63.	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemen 545! t 264!. et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete
DETAIL The state names of and expected depths to objective sands; show sizes ing points, and all other states of the states of	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer 1545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling
DETAIL The steenames of and expected depths to objective sands; show sizes ing points, and all other steenames of an analysis of 11-3/4" OD casing set as an 3534' of 8-5/8" OD casing seement first string with 400 sates of 13'. Circulate 4 hours between the same of 1300 sacks of TLW plus 100 soon of 1300 p.M. 4-7-63. Setted 8-5/8" OD casing for 30 percent for 30	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer 1545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling
DETAIL ate names of and expected depths to objective sands; show sizes ing points, and all other states of 11-3/4" OD casing set as an 3534' of 8-5/8" OD casing seement first string with 400 sates of 13'. Circulate 4 hours between the 1300 sacks of TLW plus 100 soon P.M. 4-7-63. ested 8-5/8" OD casing for 30 rested 8-5/8" OD casing for 30 rested 8-5/8"	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemen 545! t 264!. et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete
DETAIL The state names of and expected depths to objective sands; show sizes ing points, and all other states of the states of	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer 1545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling
DETAIL The state names of and expected depths to objective sands; show sizes ing points, and all other states of the states of	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer her important proposed work) 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling Job complete 12:00 A.M. 4-9-63.
DETAIL The state names of and expected depths to objective sands; show sizes ing points, and all other states of the states of	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer her important proposed work) 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling Job complete 12:00 A.M. 4-9-63.
DETAIL Tate names of and expected depths to objective sands; show sizes ing points, and all other states of the s	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer 1545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling
DETAIL Tate names of and expected depths to objective sands; show sizes ing points, and all oil TD 3 50' of 11-3/4" OD casing set a an 3534' of 8-5/8" OD casing seement first string with 400 sacks of TLW plus 100 and 13'. Circulate 4 hours between the 1300 sacks of TLW plus 100 and 100 p.M. 4-7-63. Tested 8-5/8" OD casing for 30 and 100	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer her important proposed work) 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling Job complete 12:00 A.M. 4-9-63.
DETAIL Tate names of and expected depths to objective sands; show sizes ing points, and all other states of the s	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer her important proposed work) 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling Job complete 12:00 A.M. 4-9-63.
DETAIL tate names of and expected depths to objective sands; show sizes ing points, and all other shorts and standard sandard	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer her important proposed work) 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling Job complete 12:00 A.M. 4-9-63.
DETAIL ate names of and expected depths to objective sands; show sizes ing points, and all oil TD 3 50° of 11-3/4" OD casing set a an 3534° of 8-5/8" OD casing seement first string with 400 sates and 130°. Circulate 4 hours between the 1300 sacks of TLW plus 100°. The 1300 plus 100°. Test 0.K. as ted 8-5/8" OD casing for 30° and with 1500 psi. Test 0.K. and the plan of work must receive approval in which the plan of work must receive approval in which plan of the plan of work must receive approval in which plan of the plan of work must receive approval in which plan of work must receive approval in which plan of the plan of work must receive approval in which plan of the plan of work must receive approval in which plan of the plan of work must receive approval in which plan of the pla	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer her important proposed work) 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling Job complete 12:00 A.M. 4-9-63.
DETAIL ate names of and expected depths to objective sands; show sizes ing points, and all of the sands of t	LS OF WORK s, weights, and lengths of proposed casings; indicate mudding jobs, cemer her important proposed work) 545! t 264! et at 3545!. DV tool at 2505!. cks of Incor neat. Plug at en stages. Second stage cemented sacks Incor neat. Job complete minutes before and after drilling Job complete 12:00 A.M. 4-9-63.