

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instruction
verse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Las Cruces 060942

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Justis

9. WELL NO.

3-X

10. FIELD AND POOL, OR WILDCAT

Justis-Blinebry

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 11, T-25-S, R-37-E,
N.M.L.M.

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ **Dec 31 1 32 PM '63**

2. NAME OF OPERATOR
The Atlantic Refining Company

3. ADDRESS OF OPERATOR
P. O. Box 1978, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
355' FSL, 990' FFL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3134' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☒(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8-3/4" hole to 6152' T.D. Ran logs. Ran 172 jts of 5-1/2" 14# & 15.5# casing= 6132.22'. Set at 6144.52' & cemented w/354 sx incor cement. Plug down at 6125 PM 12/22/63. Top of cement at 2400' by temperature survey. Tested 5-1/2" casing w/1800W for 30 minutes. OK & job complete at 7:00 PM 12/26/63 after 96 hrs WOG. Perforated Blinebry 5234-5300' (ES) w/4 JMT. Treated perms w/500 gal mud acid, 500 gal 15% LSTNE, 15,000 gallons lease crude containing 18,000 20/40 sand. Ran 2-3/8" tubing & IW packer for completion. Tubing bottomed at 5224.23'.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. L. L. L.

TITLE

District Drilling Supervisor

DATE

12-31-63

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

DATE

DEC 31 1963

*See Instructions on Reverse Side

E. G. HUBBLE
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.