



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **New Mexico**Lease No. **LG 067081**Unit **1**

MAR 28 1961

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, March 27, 1961

Well No. **1** is located **660** ft. from **{N}** line and **1940** ft. from **{E}** line of sec. **22**
SE/4SW/4 22 **25s** **35 e** **MDPM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated **Lea** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Lease designated Elliott Federal.

7" cemented @ 354. Drilled 6-1/4" hole to 1800' ran logs and no show.

well to be plugged following manner: 10 sx cement plug on bottom; 20 sx cement plug 3300-3400; 20 sx cement plug 1100-1200; 20 sx cement plug 300-400; 15 sx cement plug at surface. Intervals between plugs to be filled with mud. Set USGS marker and clean up location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **CACTUS DRILLING CORPORATION**Address **P O Box 32**
Midland, TexasBy *Billy Mathis*

Title _____

100

100

10