

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 01995

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Langlie "D"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Justis (Blinebry)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 14-25S-37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3105

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☒
☒

REPAIRING WELL

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out retainer @ 5567' and drilled cement to 5800'.
Perf. Lower Blinebry w/3/8" jet holes @ 5550, 76, 80, 5608, 18, 32, 44, 70, 90, 94, 5704, 16, 28, 52, 63. Frac w/20,000 gal 9# brine, 27,500# sand. Flushed w/230 bbls. brine. Mixed 3000# salt block, followed by 348 bbls. slick water. Pumped 266 bbls. brine w/15 ball sealers. Spotted 300 gals 15% HCL acid. Treated w/1700 gals acid & 20 ball sealers. Frac w/20,000 gals 9# brine & 30,000# sand.
Perf. Upper Blinebry @ 5123, 65, 87, 92, 5204, 16, 20, 24, 32, 42, 48, 80, 86, 92, 5324, 28, 42, 50. Spotted 500 gal 15% HCL acid on upper perfs. Frac w/20,000 gal 9# brine & 30,000# sand. Flushed w/230 bbls. water. Mixed 3000# rock salt in 2-1500 stages. Each stage followed by 250 gals acid. Frac w/20,000 gal 9# brine & 26,000# sand. Flushed w/230 bbls. water.
Put well on pump.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. M. Mann

TITLE District Drlg. Supt.

DATE 6-20-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

GORDON
DISTRICT ENGINEER

*See Instructions on Reverse Side