

OWWO

COUNTY LEA FIELD Justis STATE NM MN 20533

OPR GULF OIL CORP. MAP

8 Stuart, J. A.

Sec 11, T-25-S, R-37-E

CO-ORD

330' FNL, 990' FWL of Sec

Re-Cmp 4-12-72	CLASS		EL	
	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING 9 5/8" at 1159' w/500 sx 7" at 6200' w/450 sx				
LOGS EL GR RA IND HC A				
TD 6200'; PBD 5965'				

(Blinebry) Perfs 5209-5562' NO NEW POTENTIAL

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 5965' TYPE WO
DATE

F.R.C. 4-29-72; Opr's Elev. 3135' DF
PD 5965' WO (Blinebry)
(Orig. comp 11-6-63 thru (Blinebry) Perfs 5416-
5562' & (Tubb-Drinkard) Perfs 6004-6152',
OTD 6200', OPB 6164')

4-24-72 TD 6200'; PBD 5965'; COMPLETE
PB to 5965'

Perf 5209-13', 5246-50', 5286-90', 5312-16',
5373-77' w/2 SPF

Acid (5209-5377') 1200 gals (15% NE)
Frac (5209-5377') 35,000 gals wtr + 60,000#
sd

4-29-72 COMPLETION REPORTED

COUNTY	Lea	FIELD	Justis, North	STATE	N.M.	NO.
OPR.	Gulf Oil Corporation			MAP		
NO.	8	LSE	Stuart, J.A.			
SEC.	11	T.	25S	R.	37E	SUR. CO-ORD.
LOC.	330' fr N Line & 990' fr W Line of Sec.					
MI.	FROM 11-6-63(B)			CLASS.	EL 3/358	
SPUD.	9-23-63	COMP.	11-7-63(TD)	FORMATION	DATUM	FORMATION DATUM
TRT.				LOG:		
				Glor	4843	
CSG. & SX.				Bli	5346	
9 5/8"	1159'	500		Tubb	5985	
7"	6200'	450				
TBG.	DEPTH	SIZE				
LOGS	EL	GR	RA	IND	HC	A
				TD	6200'	PB 6164'
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P. T. P. HRS. TEST
5416-5562'	Flwd 509 BOPD + 22	20/64"	493	37.3	200#	356# 3hr15
(Blinebry)	BWP		min/69 BO + 3 bbls wtr			
6004-6152'	Flwd 487 BOPD + 41	24/64"	450	36.8	129#	3 1/2
(Tubb-Drinkard)	BWP		hr test 71 BO + 6 BW			
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.						
CONT.	Lea	erwood Drlg. Co.	PROP	DEPTH	6150'	TYPE
DATE						

F.R. 9-26-63
 PD 6150', Tubb-Drinkard.
 Contractor - Leatherwood Drlg. Co.

9-30-63 Drlg. 1970' anhy. & salt.
 10-7-63 Drlg. 3840' lm & dolo.
 10-14-63 Drlg. 5870' lm & dolo.
 10-21-63 TD 6200', PB 6164', prep to perf.
 10-28-63 TD 6200', PB 6164', tstg.
 Perf 6004-06', 6030-32', 6044-46', 6056-58',
 6110-12', 6129-31', 6150-52', w/2 SPF,
 Frac 18,000 gal oil + 18,000# sd.
 Recovered load., flo 194 BO + 49 BW/24 hrs thru
 26/64" chk, TP 100-200#, CP 600#.

11-4-63 TD 6200', PB 6164', tstg.
 Perf (Bline) 5416-20', 5429-33', 5479-83',
 5558-62', w/2 SPF, Frac. 5000 gal + 10,000# sd.
 Rec. load. & flo 144 BO + 39 BW/24 hrs thru
 20/64" chk, TP 500#.

11-11-63 TD 6200', PB 6164', COMPLETED.