

OWWO

COUNTY	FA	FIELD	Paduca	STATE	NM MN 20907
OPH	TENNECO OIL CO.			MAP	
	6 Monsanto - State				
	Sec 16, T-25-S, R-32-E			CO-ORD	
	1650' FSL, 2310' FWL of Sec				
	Re-Spd 1-5-70		CLASS	OWDF EL 2310	
	Re-Cmp 1-9-70		FORMATION	DATUM	FORMATION DATUM
CSG & SX - TUBING 8 5/8" at 364' w/125 sx 4 1/2" at 4739' w/150 sx					
LOGS EL GR RA IND HC A			TD 4739'; PBD 4709'		
(Delaware Sand) Perfs 4590-4620' NO NFW POTENTIAL.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4620'	TYPE WO
ATE			

8-11-70	F.R.C. 8-13-70; Opr's Elev. 3424' KB PD 4620' WO (Delaware Sand) (Orig. comp 4-5-64 thru Perfs 4614-17', OTD 4739', OPB 4709')
8-13-70	TD 4739'; PBD 4709'; COMPLETE Perf 4590-4620' w/1 SPF Acid (4590-4620') 500 gals Frac (4590-4620') 12,000 gals oil + 30,000# sd COMPLETION REPORTED

COUNTY	LEA	FIELD	Paduca	STATE	N.M.
OPR	TENNECO OIL COMPANY				MAP
6 Monsanto-State					
Sec. 16, T-25-S, R-32-E				CO-ORD	
1650' fr S Line & 2310' fr W Line of Sec.					
Spud 3-17-64		CLASS		EL 3422E	
Comp 4-5-64		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG:				
	Del sd 4588				
	Ford 4624				
	Olds 4634				
8 5/8" 364' 125					
4 1/2" 4739' 150					
LOGS EL GR RA IND HC A					
		TD 4739', PBD 4709'			

IP Delaware 4614-17' Flwd 112 BOPD. Pot. Based on 15 hr test of 70 BO thru 16/64" chk., TP 500#, gravity 41., GOR 930.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT	Ray Smith Drlg. Co.	PROP DEPTH	4800'	TYPE
DATE				

F.R. 3-19-63
 PD 4800' - Delaware
 Contractor - Ray Smith Drlg. Co.
 3-23-64 Drlg. 4205' salt & anhy.
 3-30-64 TD 4739', prep to perf.
 Cored 4585-4635', rec 50' being: 11' shly sd., w/fair show, 13' shly sd., NS, 13' sd., w/good show, 13' sd. & sh., NS.
 Cored 4635-85', rec 50' being: 3' sd. & sh., NS, 16' shly sd., w/scatt. show, 26' sd., w/scatt. sli. show, 5' sd. & sh., NS.
 Cored 4685-4735', rec 50' sd. & sh., NS.
 4-6-64 TD 4739', PBD 4709', COMPLETED
 Perf 4614-17' W/4 SPF
 Ac. 250 gals.
 Could not break formation
 Re-Perf 4614-17' W/4 SPF
 Ac. 250 gals.
 Frac 1000 gals oil + 1500# sd.