

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other Instructions
verse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

10-002592 (b)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		6. INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR TEXACO Inc.		7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P. O. Box 728 - Hobbs, New Mexico		8. FORM OR LEASE NAME O. O. Frisbie "b" NCT-2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Well located 1980' from the North Line, and 1979' from the East of Section 35, T-24-S, R-37-E, Lea County, New Mexico		9. WELL NO. 3
14. PERMIT NO. Regular		10. FIELD AND POOL, OR WILDCAT Glorieta Blindbry
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3184' (D. F.)		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35, 24-S, R-37-E
		12. COUNTY OR PARISH Lea
		13. STATE N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Total Depth - 6200'
8 5/8" Casing Cemented at 3450'

Ran Glorieta Zone: Ran 6187' of 2 7/8" O. D. Casing, 6.50 LB, J-55, NEW, and cemented at 6199'. Plug at 6190'.

Ran Blindbry Zone: Ran 6187' of 2 7/8" O. D. Casing, 6.50 LB, J-55, NEW, and cemented at 6199'. Plug at 6190'.

Cemented above strings of 2 7/8" O. D. Casing at 6199' with 400 Sx. Class "C" 4% gel with FRA, plus 450 Sx. Class "C" 4% gel, followed with 500 gals. acetic acid in each string. Job complete 6:00 P. M. June 25, 1964. Tested above strings for 30 minutes with 1500 P. S. I. from 7:00 P. M. to 7:30 P. M. June 27, 1964. Tested O. K. Job complete 7:30 P. M. June 27, 1964.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. E. Morgan

TITLE

Assistant to the District
Superintendent

DATE

June 29, 1964

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE