

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

FE-
re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032592 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C.C. Fristoe A Fed. NCT-2

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Justis Blinebry

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T-25-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State regulations.
See also space 17 below.)
At surface

990' FSL & 405' FEL of Section 3, T-25S, R-37E,
Unit Letter 'P', Lea County, New Mexico.

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3147' (DF)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

1. Rigged up.
2. Set CIBP @ 6061' & spot 35' cement on plug. PBD 6026'.
3. Squeeze csg perfs. 5375-5410' w/75 sx. Class 'C' Neat cement. Cement 2-7/8" csg annulus w/800 sx. Halliburton Lite followed by 100 sx. Class 'C' cement. Job complete 10:00 A.M., 3-11-78. WOC.
4. Perforate 2-7/8" OD csg w/2 JSPF @ 5596', 5661', 73', 5782', 86', 5804', 09', 14' & 5819'.
5. Set pkr. @ 5712'. Acidize perfs 5782-5819' w/1500 gals. 15% HCL-NE acid, 500# rock salt & 250# Benzoic Acid Flakes in 6-equal stages. Flush w/18 bbls. treated water.
6. Set RBP @ 5700' & pkr @ 5340'. Acidize perfs. 5596-5673' w/750 gals. 15% HCL-NE acid, 200# rock salt & 100# Benzoic Acid Flakes in 3-equal stages. Flush w/17 bbls. treated water.
7. Install pumping equipment. On 24 hr. potential test ending 5-9-78, well pumped 5 BO, 13 BW & GOR 1724.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Asst. District Supt.

DATE 5-12-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

MAY 15 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
JAN 11 1978
FBI - NEW YORK
100-100000-100000