

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYCOPY TO O. O. C.  
SUBMIT IN TRIP  
(Other instruction.  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032592 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NONE

7. UNIT AGREEMENT NAME

NONE

8. FARM OR LEASE NAME

C. C. Fristoe "b" NCT-2

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Und. Glorieta Gas  
Just Blinebry - Tubb Drk11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 35, T-24-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR TEXACO Inc.

3. ADDRESS OF OPERATOR P. O. Box 728 - Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surfaceWell located 1650' from the West Line, and 852' from the  
North Line of Section 35, T-24-S, R-37-E, Lea County, N.M.

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3195' (D. F.)

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*Total Depth - 6250'  
9 5/8" O. D. Casing Cemented at 949'Undesignated Tubb Drinkard Zone: Ran 6236' of 2 7/8" O. D. Casing, 6.50 LB, NEW, J-55, and  
cemented at 6247', collar at 6215', 10' sub at 5795'.Undesignated Glorieta Gas Zone: Ran 6236' of 2 7/8" O. D. Casing, 6.50 LB, NEW, J-55, and  
cemented at 6247', collar at 6215', 6' sub at 4819'.Justis Blinebry Zone: Ran 6236' of 2 7/8" O. D. Casing, 6.50 LB, NEW, J-55, and  
cemented at 6247', collar at 6215', 8' sub at 5479'.Cemented above strings of 2 7/8" O. D. Casing with 850 Sx. Class "C" 4% gel, (first 400 Sx  
with FRA). Job complete 2:00 P. M. September 25, 1964.Tested 2 7/8" O. D. Casing for 30 minutes (all strings) with 1500 P. S. I. from 8:00 A. M.  
to 8:30 A. M. September 28, 1964. Tested O. K. Job complete 8:30 A. M. September 28, 1964.

18. I hereby certify that the foregoing is true and correct

SIGNED

*H. D. Raymond*  
H. D. Raymond

TITLE

Assistant District  
Superintendent

DATE

September 30, 1964.

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

DATE

CONDITIONS OF APPROVAL, IF ANY:

OCT 2 1964

\*See Instructions on Reverse Side  
GORDON  
ACTING DISTRICT ENGINEER