

|                                          |             |           |        |           |          |
|------------------------------------------|-------------|-----------|--------|-----------|----------|
| COUNTY                                   | DA          | FIELD     | Justis | STATE     | Nr1      |
| OPR                                      | TEXACO INC. |           |        | MAP       |          |
| 9 Fristoe, C. C. "b" (NCT-2)             |             |           |        |           |          |
| Sec. 35, T-24-S, R-37-E                  |             |           |        | CO-ORD    |          |
| 852' fr N Line & 1650' fr W Line of Sec. |             |           |        |           |          |
| Spud 9-2-64; Comp 10-6-64 (Bli);         |             |           |        | CLASS     | EL 3195' |
| Comp 10-6-64 (Drkd)                      |             | FORMATION | DATUM  | FORMATION | DATUM    |
| CSG & SX - TUBING                        |             | LOG:      |        |           |          |
| 9 5/8"                                   | 949'        | 500       | SA     | 3695      |          |
| 2 7/8"                                   | 6215')      |           | Glor   | 4752      |          |
| 2 7/8"                                   | 6247')      | 850       | Bli    | 5104      |          |
| 2 7/8"                                   | 6247')      |           | Tubb   | 5802      |          |
|                                          |             |           | Drkd   | 6002      |          |
| LOGS EL GR RA IND HC A                   |             |           |        |           |          |
| TD 6250', PBD 6215'                      |             |           |        |           |          |

IP Blinebry Perfs 5544-5720' Flwd 156 BOPD. Pot. Based on 10 hr test of 65 BO thru 24/64" chk., CP 325#, gravity 37., GOR 5154.  
 IP Drinkard Perfs 6106-68' Flwd 18 BOPD + 3 BW. Pot. Based on 24 hr test thru 30/64" chk., CP 50#, gravity 36., GOR 12,611.

Distribution limited and publication prohibited by subscribers' agreement.  
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

|       |                  |      |
|-------|------------------|------|
| CONT. | PROP DEPTH 6250' | TYPE |
| DATE  |                  |      |

F.R. 9-3-64  
 PD 6250' - Glorieta, Blinebry & Tubb-Drinkard  
 9-8-64 Drlg. 2781' lm.  
 9-14-64 Drlg. 4474' lm.  
 9-21-64 Drlg. 5947' lm.  
 9-28-64 TD 6250', PBD 6215', prep to perf.  
 10-5-64 TD 6250', PBD 6215', swbg.  
 Perf (Blinebry) @ 5544', 5597', 5607', 5612',  
 5616', 5638', 5653', 5679', 5704', 5720' W/1 SPI  
 Ac. 336 gals (MA)  
 Swbd load  
 Re-Ac. 2000 gals 5544-5720'  
 Swbd 36 BLO + 10 BAW/13 hrs.  
 Frac 15,000 gals oil + 15,000# sd. 5544-5720'.  
 Flwd 393 BLO + 32 BNO/44 hrs thru 24/64" chk.

10-5-64 - cont. -

Perf (Drinkard) @ 6106', 6114', 6124', 6128',  
6134', 6142', 6148', 6156', 6160', 6168' W/1  
SPI

Ac. 500 gals.

Swbd load.

Re-Ac. 3000 gals. 6106-6168'

Flwd 26 BNOPD + 4 BWPD thru 30/64" chk.,

Perf (Glorieta) @ 4898', 4909', 4913', 4917'  
W/2 SPF

10-12-64 TD 6250', PBD 6215', tstg Glorieta

Swbd 12 BFW in 13 hrs from 4898-4917'

Squeezed Perfs 4898-4917' W/35 sx.

Perf (Glorieta) @ 4834', 4840', 4852', 4856',  
4859', 4866', 4870' W/1 SPI

Ac. 500 gals., had communications.

10-19-64 TD 6250', PBD 6215', swbg load.

Set BP @ 4885' & Pkr @ 4808'

Ac. 500 gals. perfs 4834-70'

Swbd dry.

Re-Ac. 2000 gals. 4834-70'.

Swbd 78 BAW/6 hrs.

Frac 10,000 gals wtr + 10,000# sd. 4834-70'.

Swbd 110 BLW/6½ hrs.

10-26-64 TD 6250', PBD 6215', prep to squeeze Glorieta.

Swbd 25 BFW in 5 hrs, w/sli show gas 4834-70'.

11-2-64 TD 6250', PBD 6215', fshg swab line.

Squeezed Glorieta Perfs 4834-70' W/50 sx.

Perf (Queen) @ 3349', 3353', 3383', 3385',  
3412', 3425', 3496', 3503' W/1 SPI

Ac. 2000 gals.