

F.R.C. 10-10-68; OWWO  
PD 5802' - Blinebry & Tubb-Drinkard  
(Orig. Cmp 4-29-64 thru Blinebry perfs 5287-  
5549' & 4-28-64 thru Tubb-Drinkard perfs  
5817-6127', OTD 6200')  
10-7-68 TD 6200', COMPLETE  
Perf (Tubb-Drinkard) 5790-5802' W/2 SPF  
Perf (L/Blinebry) @ 5578', 5592', 5620',  
5649', 5661', 5680', 5688', 5720, 5740',  
5758' W/1 SPI  
Perf (U/Blinebry) @ 5060', 5080', 5088',  
5094', 5104', 5106', 5113', 5134', 5148',  
5168', 5189', 5201', 5216', 5239', 5245'  
W/1 SPI

LEA Justis NM  
UNION TEXAS PET. CORP., #2 Justis

Sec. 11-25S-37E  
Page #2

10-7-68

Cont.

Acid (5790-6127') 1500 gals.

Frac (5790-6127') 60,000 gals wtr + 90,000#  
sd.

Acid (5060-5758') 2000 gals.

Frac (5060-5758') 80,000 gals wtr + 120,000#  
sd.

|                                                                                                                                                     |  |                            |       |                   |       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------|-------|-------------------|-------|
| COUNTY <u>LEA</u>                                                                                                                                   |  | FIELD <u>Justis, North</u> |       | STATE <u>N.M.</u> |       |
| OPR <u>UNION TEXAS PETROLEUM CORPORATION</u>                                                                                                        |  |                            |       | MAP               |       |
| <u>2 Justis-Federal</u>                                                                                                                             |  |                            |       |                   |       |
| <u>Sec. 11, T-25-S, R-37-E</u>                                                                                                                      |  |                            |       | CO-ORD            |       |
| <u>1650' fr S Line &amp; 990' fr E Line of Sec.</u>                                                                                                 |  |                            |       |                   |       |
| <u>Spud 2-15-64; Comp 4-29-64 (Bli);</u>                                                                                                            |  |                            |       | CLASS             |       |
| <u>4-28-64 (T-D)</u>                                                                                                                                |  |                            |       | EL <u>31475</u>   |       |
| CSG & SX - TUBING                                                                                                                                   |  | FORMATION                  | DATUM | FORMATION         | DATUM |
| LOG:                                                                                                                                                |  |                            |       |                   |       |
| Blinebry                                                                                                                                            |  |                            |       |                   |       |
| 9 5/8" 958' 100                                                                                                                                     |  | 5040                       |       |                   |       |
| 7" 6200' 632                                                                                                                                        |  |                            |       |                   |       |
|                                                                                                                                                     |  |                            |       |                   |       |
|                                                                                                                                                     |  |                            |       |                   |       |
|                                                                                                                                                     |  |                            |       |                   |       |
| LOGS EL GR RA IND HC A                                                                                                                              |  |                            |       |                   |       |
|                                                                                                                                                     |  | TD 6200'                   |       |                   |       |
| IP Blinebry Perfs 5287-5549' Flwd 143 BOPD + 9 BW. Pot. Based on 24 hr test thru 10/64" chk., TP 805#, gravity 36.                                  |  |                            |       |                   |       |
| IP Tubb-Drinkard Perfs 5817-6127' Flwd 156 BOPD + 1 BW. Pot. Based on 24 hr test thru 10/64" chk., IP 580#, gravity 35.                             |  |                            |       |                   |       |
| Distribution limited and publication prohibited by subscribers' agreement.<br>Reproduction rights reserved by Williams & Lee Scouting Service, Inc. |  |                            |       |                   |       |
| CONT.                                                                                                                                               |  | PROP DEPTH                 |       | 6200' TYPE        |       |
| DATE                                                                                                                                                |  |                            |       |                   |       |

F.R. 2-6-64  
 PD 6200' - Blinebry & Tubb-Drinkard  
 2-17-64 Drlg. 704'.  
 2-24-64 Drlg. 2661'.  
 3-2-64 TD 3630', fshg.  
 3-9-64 Drlg. 4505'.  
 3-16-64 Drlg. 5524'.  
 3-23-64 TD 6200', running casing.  
 3-30-64 TD 6200', prep to rec load.  
 Perf (Drinkard) @ 5934', 5938', 5941', 5945',  
 5952', 5963', 5978', 5985', 5992', 6000', 6008',  
 6010', 6026', 6039', 6054', 6066', 6075', 6082', 6089',  
 6102', 6118' & 6127' W/1 SPI  
 Ac. 2500 gals.  
 Flwd 20 BLO & died.  
 Frac 15,000 gals oil + 16,000# sd.  
 4-6-64 TD 6200', milling on junk  
 Flwd back load from Drinkard 5934-6127'  
 4-13-64 TD 6200', CO sand.

4-20-64 TD 6200', prep to perf Blinebry  
Perf (Tubb) @ 5817', 5820', 5824', 5834',  
5839', 5844', 5847', 5858', 5873', 5879',  
W/1 SPI  
Ac. 2000 gals.  
Frac 15,000 gals oil + 16,000# sd. 5817-79'  
Flwd 742 BLO in 13 hrs.

4-27-64 TD 6200', SI for Pkr Leakage.  
Perf (Blinebry) @ 5287', 5294', 5308', 5314',  
5337', 5340', 5360', 5365', 5371', 5399', 5417',  
5422', 5427', 5434', 5444', 5459', 5464', 5474',  
5481', 5486', 5504', 5545' & 5549' W/1 SPI  
Ac. 2500 gals.  
Frac 20,000 gals oil + 20,000# sd. 5287-5549'  
Flwd 670 BLO/13 hrs thru 3/4" chk.

5-4-64 TD 6200', COMPLETED.