

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved,
Budget Request No. 42-21421

GEOLOGICAL SURVEY

4. LEASE ORIGINATOR AND SERIAL NO.

LC-032511 (F)

6. IF INDICATED, ALLOTTEE OF TRIDE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug hole a different reason, etc.)
Use "APPLICATION FOR PERMIT" for such purposes.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR UNION TEXAS PETROLEUM CORPORATION		8. FARM OR LEASE NAME Stuart
3. ADDRESS OF OPERATOR 1300 Wilco Building, Midland, Texas 79701		9. WELL NO. 8
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FNL & 990' FWL		10. FIELD AND POOL, OR WILDCAT Justis (Blinebry)
14. PERMIT NO.		11. SEC., T., R., E., OR NECK AND SURVEY OR AREA Sec. 11, T-25-S, R-37-E
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 3125' DF		12. COUNTY OR PARISH (3. STATE Lea New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report on Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. August 13, 1975, re-entered well and pulled tubing, rods & pump. (Installed BOP).
2. Ran tubing, packer and retrievable bridge plug. Set BP @ 5655' & packer at 5392' and acidized perfs. w/5000 gals. 15% NE Acid.
3. August 14, 1975, perforated additional Blinebry interval w/1 JSPF 5214, 5218, 5224, 5228, 5234, 5242, 5246, 5253, 5260, 5266, 5276, 5284, 5293, 5303, 5307, 5312, 5320, 5326, 5335, 5340, 5350, 5355, 5362, 5370 & 5383' (Total 25 holes).
4. Acidized perfs. 5214-5383' w/2500 gals. NE Acid.
5. August 18, 1975, sand frac'd Blinebry perfs. w/30,000# 20/40 sand, 30,000 gals. gelled SW and 300# rock salt & 300# Benzoic acid flakes.
6. August 19, 1975, reversed out sand and retrieved retrievable bridge plug.
7. August 20, 1975, ran rods, tubing and pump. Placed well back on production.

18. I hereby certify that the foregoing is true and correct.

SIGNATURE

Stanley A. Post

TITLE Gas Measurement Analyst

DATE 9-3-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

