

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on reverse side)Form approved  
Bureau of Reclamation, No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 032511 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

P. J. Langlie "B"

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Justis Blinbry

11. SEC., T., R., M., OR BLM. AND  
SURVEY OR AREA

14-25-37

NMPM

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Pan American Petroleum Corporation

3. ADDRESS OF OPERATOR

Box 68 - Hobbs, New Mexico - 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

330' FSL X 990' FWL, Sec. 14, (Unit M, SW/4 SW/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3103' RDB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 5730'; PBD 5645'; 4-1/2" CSA 5730 W/925 sx.

Perf's 5503-07', 5522-24', 5534-38', 5544-48', 5570-77' 5601-04'

In order to increase productivity of well the following remedial work is proposed.

"Set retainer at approx. 5485' and squeeze existing perforations with 100 sx Incor plus 8% Halad-9.

Perforate 5298', 5307', 5319', 5334', 5352', 5373', and 5431' W/1 SPF.

Acidize with 2000 gallons

Swab and test

RECEIVED

JUN 1 1964

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Superintendent

DATE

5/28/64

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

\*See Instructions on Reverse Side

