				TE•	Form approved. Budget Bureau No. 42-R1424
D		(IMEN: OF THE INTERIOR verse side)			5. LEASE DESIGNATION AND SERIAL NO.
GEOLOGICAL SURVEY					NM-053646-A
SUNDR	Y NOTICES, AND RE	EPORTS (ON WELLS		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use this form for proposals to drill of to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT"— proposals.)					NONE
Use "APPLICATION FOR PERMIT—Paper and proposals.)					
OIL CAR DED					7, UNIT AGREEMENT NAME NONE
2. NAME OF OPERATOR					8. FARM OR LEADE NAME
TEXACO Inc.					C. Elliott Federal
P. O. Box 728 - Hobbs, New Mexico					9. WELL NO.
					1 等以集 医激素。
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface					10. FIELD AND POOL, OR WILDCAT
					Jal - Strawn Gas
Well located 1980' from the South Line, and 1980' from the					11. SEC;, T., R., M., OR BLK. AND SUBVEY OR AREA
East Line of Section 8, T-25-S, R-36-E, Lea County, New Mexico.					Sec. 8, T-25-S, R-36-E
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)					12. COUNTY OR PARISH 13. STATE
Regular					Lea N.M.
· · · · · · · · · · · · · · · · · · ·					
`	Check Appropriate Box To	Indicate N	ature of Notice, Report, o	or Ot	her Data 🧸 🕺 🥞 🕳
NOTIC	CE OF INTENTION TO:		SUB	SEQUE	NT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASIN	a	WATER SHUT-OFF	x	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZING	L.J.	ABANDONMENT.
REPAIR WELL	CHANGE PLANS		(Other)	nlts of	f multiple completion on Well
(Other)	PLETED OPERATIONS (Clourly stat	to all postinous	Completion or Reco	omplet	ion Report and Log form.)
proposed work. If well nent to this work.) *	is directionally drilled, give su	bsurface locat	ions and measured and true ve	rtical	cluding estimated date of starting any depths for all markers and zones perti-
·					1 450 a 1 2 3 3 3 6 1
		Total De	pth - 3701		
			O A. M. August 13.	196	
Ran 344' of 1	1 3/4" O. D. Casing	, 23.72	LB, Spiral Weld, No	ew,	and cemented at 3
370' with 500 Sx. Incor neat with 2% CACL. Plug at 340'. Cem					ent Circulated - 5 3
		. 0	_		三分别的复数 二甲二异基氯醛
Temperature of mixing slurry - 82°, Strength 12 Hours - 800 P. Bottom Hole Temperature - 62°, Job complete 4:45 A. M. August					
Bottom Hole Te	emperature = 02°, J	op combT	ete 4:45 A. M. Augu	ıst	10, 1905.
Tested 11 3/h	" O. D. Casing for	30 minut	ac with 600 P C T	· .	700 A M A
to 2:30 A. M.	August 17, 1965.	Tested O	K. Drilled cemen	it n	lug and re
tested for 30	minutes with 600 P.	S. I. :	From 3:00 A. M. to	3:30	O A. M. August
17, 1965. Tes	sted O. K. Job comp	olete 3:3	30 A. M. August 17.	196	55. 5 4 2 3 5 5 6 2 8
			•		
					- 플러스 시청 - 특히 - 스윙 (1)루 - 영화 등의 - 특히 - 구성 등록
					- 임칭병활활 관련 종립 호본
					- 동생활을 등 중국 - 콜레큐스
18. I hereby certify that the for	/				
SIGNED 12. Mer	gan		istant to the Distr	rict	DATE Aurust 17, 1965
(This space for Federal or	State office use)	Si	perintendent		

to state

TITLE .