

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

5. LEASE

NM 051998

106. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Carlson B-13

9. WELL NO.

7

10. FIELD OR WILDCAT NAME

Justis Blinbry

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 13, T-25-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3,085 GL, 3,097 KB

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Terra Resources, Inc.

3. ADDRESS OF OPERATOR

10 Desta Dr. Ste 500 W, Midland, TX

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

T25S, R37E

AT SURFACE: 990' FNL & 2,200' FEL, Sec 13,

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugging Report

A) 12-4-84 Rigged up pulled out of hole rods and pump.

B) 12-5-84 Pulled 165 joints 2-3/8" tubing.

C) 12-6-84 Set CIBP @ 5,080' in 4 1/2" casing with 2 sacks cmt, TOC @ 4,100'.

D) 12-7-84 Perf 1,650' w/3-1/8" csg gun. set cmt ret. @ 1,617' with 37 sacks Cl "H" cmt. Perf @ 1250' set ret. @ 1,220' with 37 sacks Cl "H" cmt. Perf @ 1023'. Set cmt ret. @ 989' with 35 sacks Cl "H". Perf @ 100', circ 41 sacks Cl "H" cmt. to surface. Rigged down & moved off.

E) 12-8-84 Cut off casing head and welded on steel plate to 8-5/8" casing. Set marker.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Joe Amezcua

TITLE

Operations Engr.

DATE

2/20/85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 25 1985

O.C.P.
HOBBS OFFICE