

CORRECTED COPY

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

HOBBS OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION

APR 5 11 18 AM '66

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K3091

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator PAULEY PETROLEUM INC.	8. Farm or Lease Name New Mexico State
3. Address of Operator 930 Petroleum Life Bldg., Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER C , 660 FEET FROM THE North LINE AND 1980 FEET FROM West LINE, SECTION 36 TOWNSHIP 25 RANGE 34 NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3305.4' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

March 16, 1966 - Total depth 5795'.
Drilled to 5795'.

Ran Sonic-Gamma Ray Log and Laterolog and took sidewall cores.

Propose to plug and abandon, as log calculations and core analysis proves well to be non-commercial. Cement plugs will be placed as following:

10 sacks cement plug at surface,
50 sacks cement plug from 831' to 1090',
35 sacks cement plug from 5261' to 5450', and
25 sacks cement plug from 5660' to 5795'.

Note: Received verbal permission to plug and abandon well from District Office, New Mexico Oil Conservation Commission, Hobbs, New Mexico, March 16, 1966.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. C. Hammer TITLE Agent DATE April 4, 1966

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: