

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIP
(Other instructions
reverse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY

SUNDRY NOTICES, AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
See "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 0450818

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gulf-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., E., M., OR BLK. AND
SURVEY OR AREA

Sec. 20, T-25-S, R-35-E

12. COUNTY OR PARISH

Lee

13. STATE

New Mexico

1.

OIL
WELL☐GAS
WELL☐

OTHER

Wildcat

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

1405 Wilco Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FWL & 660' FWL of Section 20

14. PERMIT NO.

-

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3320.8 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Csg. setting & testing

x

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill 17 1/2" hole to 5300'. Ran Gamma Ray Sonic log. Ran 131 jets
13 3/8" 61#, 68#, 72#, J-55 & N-80 casing set @ 5300'. Cemented
w/3890 sx cement. Cement circulated back to surface. Plug down
@ 3:45 p.m., 7-5-67. WOC 24 hrs. Test BOP and wellhead to 5000#.
Test 13 3/8" @ 1000# for 30 min, hold O.K. Drilled out float collar
and guide shoe to 5300'. Tested casing @ 1000#. Drilled to 5363'.
Test casing seat @ 1000#- all hold O.K.
Drill ahead w/12 1/2" hole @ 3 a.m., July 8, 1967.

APPROVED

JUL 14 1967

A. R. BROWN
DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

SIGNED

C. H. Brown

TITLE

District Engineer

DATE

July 10, 1967

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and is approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations or Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; kind or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1965-O-682-228

5010-1081

APR 1965
DISTRICT OFFICE
ALABAMA

APR 1965

APR 1965

APR 1965