

OWWD

COUNTY TEA FIELD Justis STATE NM 30-025-22204

OP's TEXAS PACIFIC OIL CO. MAP

10 Eaton, S. W.

Sec 12, T-25-S, R-37-E CO-ORD

500' FSL 1650' FWL of Sec

		CLASS <u>OWDF</u> EL. <u>31042</u>	
Re-comp 2-11-71		FORMATION	DATUM
CSG & SX - TUBING 8 5/8" at 950' w/500 sx 5 1/2" at 6178' w/620 sx			
LOGS	EL GR RA IND HC A		

ID 6200'; FED 6142'

(Elimebry) Perfs 5103-5602' NO NEW POTENTIAL.

(Tubb-Drinkard) Perfs 5775-6138' NO CHANGE.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Spouting Service, Inc.

CONT. DATE PROF. DEPTH 5300' TYPE WO

W.R.C. 3-4-71; Opr's Elev. 3104' DF
ID 5300' WO (Elimebry)
(Orig. comp 8-26-67 thru (Elimebry) Perfs 5103-5602' & (Tubb-Drinkard) Perfs 5775-6138'; ID 6200'
OFE 6142';
3-2-71 ID 6200'; FED 6142'; COMPLETE
Perf (Elimebry) @ 5103', 5112', 5126', 5139',
5149', 5166', 5175', 5192', 5197', 5204', 5208',
5219', 5226', 5252', 5256', 5267', 5271', 5281',
5289', 5295'
Acid (5103-5602') 1500 gals 10% HCl;
Fr-c (5103-5602') 80,000 gals jelled brine +
120,000# sd (4 stages)
3-4-71 COMPLETION REPORTED

COUNTY	LEA	FIELD	Justis	STATE	NM
OPR	TEXAS PACIFIC OIL CO.				MAP
	10 Eaton S W				
	Sec. 12, T-25-S, R-37-E				CO-ORD
	500' FSL, 1650' FWL of Sec.				30-025-22204
	Spd 7-21-67; Cmp 8-26-67 (Bli)				CLASS
	Cmp 8-22-67 (T-D)				EL
	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING					
8 5/8" 950'	500				
5 1/2" 6178'	620				
LOGS EL GR RA IND HC A					
	TD 6200', PBD 6142'				
IP Blinbry Perfs 5327-5602' Flwd 144 BOPD + 136 BW. Pot.					
Based on 24 hr test thru 26/64" chk., TP 100#.					
IP Tubb-Drinkard Perfs 5775-6138' Flwd 160 BOPD + 120 BW.					
Pot. Based on 24 hr test thru 24/64" chk., TP 180#.					
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.					
CONT.	FWA Drlg. Co.			PROP. DEPTH	6200'
DATE				TYPE	RT

F.R. 7-27-67; Opr's Elev. 3104' DF
PD 6200' - Blinbry & Tubb-Drinkard
Contr. - FWA Drlg. Co.

9-11-67 AMEND FOOTAGE: Formerly reported as 550' FSL,
1650' FWL of Sec.

7-31-67 TD 4397' 1m, stuck DP.

8-7-67 Drlg. 5425' 1m.

8-14-67 TD 6200', WOC.

8-21-67 TD 6200', PBD 6142', prep frac.
Perf @ 5775', 5780', 5785', 5790', 5794',
5820', 5837', 5862', 5869', 5881', 5963',
5988', 6052', 6060', 6074', 6079', 6103',
6111', 6123', 6132', 6138' W/1 SP1
Acid (5775-6138') 2500 gals.
Swbd 26 BO + 94 RLW in 8 hrs.

8-28-67 TD 6200', FSD 6142', swbg.
Frac (5775-6138') 30,000 gals brine +
30,000# sd.
Flwd 160 BO + 120 BW in 24 hrs.,
thru 24/64" chk., TP 180#, CP 1050#
(5775-6138')
Perf (Blinebry) @ 5327', 5369', 5398',
5408', 5428', 5435', 5457', 5510', 5522',
5530', 5557', 5595', 5602' W/1 SPI
Acid (5327-5602') 2500 gals (15%)
Swbd 40 BO + 20 BLW in 4 hrs.
9-5-67 TD 6200', PBD 6142', tstg.
Acid (5327-5602') 7500 gals.
Swbd & Flwd 75 BO + 6 BW in 12 hrs (5327-5602')

Frac (5327-5602') 25,000 gals brine +
25,000# sd.
Flwd 144 BO + 136 BLW in 24 hrs thru
26/64" chk., TP 100#, CP 600#. (5327-5602')
9-11-67 TD 6200', PBD 6142', COMPLETE
LOG TOPS: Anhy 1048', Tansil 2243', Yates
2387', Seven Rivers 2646', Queen 3108', Penrose
3220', Grayburg 3416', San Andres 3632', Glor.
4702', Blinebry 5095', Tubb Marker 5720',
Tubb Sand 5769', Drinkard 5971'.