

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME NMFU	
2. NAME OF OPERATOR Continental Oil Company		8. FARM OR LEASE NAME JACK B 26	
3. ADDRESS OF OPERATOR Box 460 Hobbs N.M. 88240		9. WELL NO. 3	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL + 660' FWL of Sec 26		10. FIELD AND POOL, OR WILDCAT Justis Blinberry Pool	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3218' DF	
		12. COUNTY OR PARISH Lea	
		13. STATE N.M.	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

Stimulate

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

It is proposed to stimulate the subject well with the following procedure:

Tag fill. If above 5695' run bit & scraper to clean out to 5750'. Set retrievable squeeze packer at 5131'. Acidize with 3000 gals. Paragon acid dispersion. Flush tbq. with 25 bbls. 20% KCL water w/ gal./100 gal. adomall. Swab back acid load. Pull retrievable packer. GIH w/ tbq. Set tbq. at 5639', SM @ 5660', mud anchor at 5691'. Put well back on production.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Butterfield

TITLE

ADMIN. SUPERV.

DATE 6-7-77

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUN 8 1977

BERNARD MCROZ  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side

USGS(6), NMFU(4), File

RECEIVED

JUN 14 1977

CE CONGRESSIONAL COMM.  
WASH. D. C.

6-10-77